

# Top Load Washer Specifications

	SWNLC SWNLY	SWTT20, SWTT21, SWTY20, SWTY21	SWT820, SWT821 SWT910, SWT911 SWT920, SWT921
<b>Control</b>	Quantum Gold	MDC (Micro-Display Control)	Electromechanical
<b>Basket/Cylinder Volume</b> - cu. ft. (liters)	3.16 (89)	2.8 (79)	2.8 (79)
<b>Width</b> - in (mm)	25 5/8" (651)	25 5/8" (651)	25 5/8" (651)
<b>Depth</b> - in (mm)	28" (711)	28" (711)	28" (711)
<b>Height*</b> - in (mm)	43" (1092)	43" (1092)	43" (1092)
<b>Work Surface Height</b> - in (mm)	36" (914)	36" (914)	36" (914)
<b>Weight</b> - lb (kg)	190 (86)	190 (86)	190 (86)
<b>Shipping Weight</b> - lb (kg)	210 (95)	210 (95)	210 (95)
<b>Cycle Time</b> - minutes	Programmable	16-28	16-28
<b>Motor HP</b>	2-speed, 1/2 HP	2-speed, 1/2 HP	SWT910, SWT911 - 1-speed, 1/2 HP SWT820, SWT821, SWT920, SWT921 - 2-speed, 1/2 HP
<b>Water Consumption</b> - gal. per cycle	29.7	23.7	26.6
<b>Water Factor</b> - gal. per cu. ft.	9.4	8.8	9.5
<b>Modified Energy Factor</b>	1.34	1.5	1.26
<b>Hot Water</b> - gal. per cycle	4.61	2.99	4.48
<b>Water Pressure</b> - psi (bar)	Pressure fill – 20 to 120 (1.4/8.3)	Pressure fill – 20 to 120 (1.4/8.3)	Pressure fill – 20 to 120 (1.4/8.3)
<b>Spin Speed</b> - RPM	2-spd, High 710, Low 473	2-spd, High 710, Low 473	1-spd, High 710, Low 473
<b>Cycle/Temperature</b>	Hot Normal Warm Perm Press Cold Delicate	Normal Hot Normal Warm Perm Press Warm Delicates Cold	Hot Normal Warm Perm Press Cold Delicate
<b>Electrical Specifications and Circuit Requirements</b>	120/60/1-15 amp	120/60/1-15 amp	120/60/1-15 amp
<b>Motor</b> - RPM	60 Hz: 1725 or 1140	60 Hz: 1725 or 1140	60 Hz: 1725 or 1140
<b>Agency Approval</b>	cULus	cULus	cULus
<b>Activation</b>	Coin/Card-Operated	Coin/Card-Operated	Coin/Card-Operated/Push-to-Start
<b>Self-Adjusting Rear Legs</b>	Yes	Yes	Yes
<b>Top and Lid Finish</b>	Porcelain	Porcelain	Porcelain
<b>Colors</b>	White, Bisque	White, Bisque	White, Bisque

\* Heights may vary slightly depending on leveling adjustments.

At Speed Queen, we're so confident that our heavy-duty commercial washers and dryers are Commercial Built to Last Longer, that we're offering the following limited warranty to prove it: Through three years† — Any part of the washer, dryer or stack dryer. Through five years† — The washer transmission assembly, base and cabinet assembly including top, lid and door, against rust from inside out. Lifetime\* — The stainless steel washtub.

† Parts only. Labor not included. See Speed Queen Warranty Bond for specifics.

For the most accurate information, the installation guide should be used for all design and constructions purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2000.

Printed in the U.S.A.

©Copyright 2010 Alliance Laundry Systems LLC