

	Washers	Single Load Dryers	Stack Dryers	Stack Washer/Dryers
	SFNLCF5, SFNLCFJ, SFNLYF5, SFNLYFJ	Electric: SDELCFG, SDELYFG Gas: SDGLCFG, SDGLYFG	Electric: SSELCFG5, SSELCFGW Gas: SSELYFG5, SSELYFGW, SSGLCFG5, SSGLCFGW, SSGLYFG5, SSGLYFGW	Electric: STELCF5, STELYF5 Gas: STGLCF5, STGLYF5
Basket/Cylinder Volume - cu.ft. (liters)	2.84 (80)	70 (198)	70 (198)	2.84 (80)/70 (198)
Width - in (mm)	26 7/8" (683)	26 7/8" (683)	26 7/8" (683)	26 7/8" (683)
Depth - in (mm)	28" (711)	28" (711)	28" (711)	28" (711)
Height* - in (mm)	43" (1092)	43" (1092)	76 5/8" (1946)	76 5/8" (1946)
Weight - lb (kg)	250 (113)	Electric: 150 (68) Gas: 155 (70)	Electric: 265 (120) Gas: 275 (125)	Electric: 360 (163) Gas: 365 (166)
Shipping Weight - lb (kg)	270 (123)	Electric: 160 (73) Gas: 165 (75)	Electric: 280 (127) Gas: 290 (132)	Electric: 390 (177) Gas: 395 (179)
Cycle Time - minutes (default)	27	45	45	27/45
Motor HP (Capacitor Start and Thermal Protected)	1 HP, 750W	1/3 HP, 5.5 amps	1/3 HP, 5.5 amps	1 HP, 750W 1/3 HP, 5.5 amps
Water Consumption - gal (Liter)	11.0 (41.7)	N/A	N/A	11.0 (41.7)
Water Factor - gal/ft ³ (Liters/Liter/cycle)	4.0 (0.53)	N/A	N/A	4.0 (0.53)
Modified Energy Factor - ft ³ /kWh/cycle (Liters/kWh/cycle)	2.40 (67.97)	N/A	N/A	2.40 (67.97)
Average Hot Water Usage - gal (Liter)	0.9 (3.3)	N/A	N/A	0.9 (3.3)
Water Pressure - psi (bar)	Pressure fill 20 to 120 (1.4/8.3)	N/A	N/A	Pressure fill 20 to 120 (1.4/8.3)
Spin Speed - RPM	500, 650, 1000	N/A	N/A	500, 650, 1000
Cycle/Temperature	Hot Normal Warm Perm Press Cold Delicate	High 160 ° Medium 155 ° Low 145 ° Delicate 115 ° No Heat	High 160 ° Medium 155 ° Low 145 ° Delicate 115 ° No Heat	See washer and dryer columns for corresponding cycles and temperatures.
Electrical Specifications and Circuit Requirements	120/60/1-15 amp	Electric: 120/240/60/1-30 amp Gas: 120/208/60/1-30 amp 120-60/1-15 amp	Electric: 120/240/60/1-30 amp Gas: 2 ea 120/208/60/1-30 amp 120-60/1-15 amp	See washer and dryer columns for corresponding cycles and temperatures.
Btu per Hour (kcal)	N/A	25,000 (6300)	25,000 (6300)	25,000 (6300)
Heating Element**	N/A	5350W, 240V 4750W, 208V	5350W, 240V 4750W, 208V	5350W, 240V 4750W, 208V
Type of Gas (Gas models only)	N/A	Factory-equipped natural/mixed gas convertible to LP gas***	Factory-equipped natural/mixed gas convertible to LP gas***	Factory-equipped natural/mixed gas convertible to LP gas***
Utility Connections - in (mm)	N/A	Gas: 3/8" NPT (9.5)	Gas: 3/8" NPT (9.5)	Gas: 3/8" NPT (9.5)
Air Outlet Diameter - in (mm)	N/A	4" (102)	4" (102)	4" (102)
Exhaust Airflow† - cfm (liters/sec)	N/A	220 (105)	220 (105)	220 (105)
Maximum Exhaust Static Back Pressure	N/A	0.6" W.C.	0.6" W.C.	0.6" W.C.
Agency Approval	cULus	Electric: cULus Gas: CSA Star	Electric: cULus Gas: CSA Star	Electric: cULus Gas: CSA Star
Activation	Coin/Card Op	Coin/Card Op	Coin/Card Op	Coin/Card Op
Top and Lid Finish	Porcelain	Porcelain	N/A	N/A
Colors	White	White	White	White
Door Type	Window	Solid	Solid, Window	Window

* Heights may vary slightly depending on leveling adjustments.

** Electric dryers come equipped for 120/240/60/1 operation. They can be field converted to operate on 120/208/60/1 with optional 61928 conversion kit. Gas dryers can be field converted for operation on LP gas with optional 458P3 conversion kit.

*** IMPORTANT: Any product revisions or conversions must be made by the Manufacturer's Authorized Dealers, Distributors, or local service personnel.

† Measured at point of exit from dryer.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2008.

Printed in the U.S.A.

© Copyright 2012 Alliance Laundry Systems LLC

