

| | COIN PREP COIN PREP CARD | Top Load Washers | Single Load Dryers | Stack Dryers | Front Load Washers |
|---|--------------------------------|--|--|--|---|
| | | SWNLC2P, SWNLC2S SWNLX2S, SWNLX2P SWNLY2P, SWNLY2S | Elec, Gas SDELCRG, SDGLCRG Elec, Gas SDELXRG, SDGLXRG Elec, Gas SDELYRG, SDGLYRG | Elec, Gas SSELCF, SSGLCF Elec, Gas SSELXF, SSGLXF Elec, Gas SSELYF, SSGLYF | SFNNCR SFNNYR |
| Basket/Cylinder Volume - cu.ft. (liters) | | 3.26 (92.3) | 7.0 (198) | 7.0 (198) | 2.84 (80)/7.0 (198) |
| Width - in (mm) | | 25 5/8" (651) | 26 7/8" (683) | 26 7/8" (683) | 26 7/8" (683) |
| Depth - in (mm) | | 28" (711) | 28" (711) | 28" (711) | 28" (711) |
| Height* - in (mm) | | 43" (1092) | 43" (1092) | 76 5/8" (1946) | 43" (1092) |
| Weight - lb (kg) | | 190 (86) | Electric: 135 (61) Gas: 140 (64) | Electric: 265 (120) Gas: 275 (125) | 240 (109) |
| Shipping Weight - lb (kg) | | 210 (95) | Electric: 145 (66) Gas: 150 (68) | Electric: 280 (127) Gas: 290 (132) | 260 (118) |
| Cycle Time - minutes (default) | | 27 | 45 | 45 | 27/45 |
| Motor HP (Capacitor Start and Thermal Protected) | | 1/2 HP, 375W | 1/3 HP, 5.5 amps | 1/3 HP, 5.5 amps | 1 HP, 750 W |
| Water Consumption - gal (Liter) | | 27.3 (103.2) | N/A | N/A | 11.0 (41.7) |
| Water Factor - gal/ft³ (Liters/Liter/cycle) | | 8.4 (1.12) | N/A | N/A | 4.0 (0.53) |
| Modified Energy Factor - ft³/kWh/cycle (Liters/kWh/cycle) | | 1.75 (49.6) | N/A | N/A | 2.40 (67.97) |
| Hot Water Usage - gal (Liter) | | 1.9 (7.4) | N/A | N/A | 0.9 (3.3) |
| Water Pressure - psi (bar) | | Pressure fill 20 to 120 (1.4/8.3) | N/A | N/A | Pressure fill 20 to 120 (1.4/8.3) |
| Spin Speed - RPM | | 473, 710 | N/A | N/A | 500, 650, 1000 |
| Cycle/Temperature | | Hot Warm Cold Normal Perm Press Delicate Delicate | High, Medium, Low, Delicate No Heat | High, Medium, Low, Delicate, No Heat | Hot Warm Cold Normal Perm Press Delicate Delicate |
| Electrical Specifications and Circuit Requirements | | 120/60/1-15 amp | Electric: 120/240/60/1 30 amp 120/208/60/1 30 amp Gas: 120-60/1-15 amp | Electric: 120/240/60/1 2 ea 30 amp 120/208/60/1 30 amp Gas: 2 ea 120-60/1-15 amp | 120/60/1-15 amp |
| Btu per Hour (kcal) | | N/A | 25,000 (6300) | 25,000 (6300) | N/A |
| Heating Element** | | N/A | 5350W, 240V 4750W, 208V | 5350W, 240V 4750W, 208V | N/A |
| Type of Gas (Gas models only) | | N/A | Factory-equipped natural/ mixed gas convertible to LP gas*** | Factory-equipped natural/ mixed gas convertible to LP gas*** | N/A |
| Utility Connections - in (mm) | | N/A | Gas: 3/8" NPT (9.5) | Gas: 3/8" NPT (9.5) | N/A |
| Air Outlet Diameter - in (mm) | | N/A | 4" (102) | 4" (102) | N/A |
| Exhaust Airflow† - cfm (liters/sec) | | N/A | 220 (105) | 220 (105) | N/A |
| Maximum Exhaust Static Back Pressure | | N/A | 0.6" W.C. | 0.6" W.C. | N/A |
| Agency Approval | | cULus | Electric: cULus Gas: CSA Star | Electric: cULus Gas: CSA Star | cULus |
| Activation | | Coin/Card Op | Coin/Card Op | Coin/Card Op | Coin/Card Op |
| Top and Lid Finish | | Porcelain | Porcelain | N/A | Porcelain |
| Colors | | White | White | White | White |
| Door Type | | Window | Solid | Solid, Window | Window |

* Heights may vary slightly depending on leveling adjustments.

** Electric dryers come equipped for 120/240/60/1 operation. They can be field converted to operate on 120/208/60/1 with optional 61928 conversion kit. Gas dryers can be field converted for operation on LP gas with optional 458P3 conversion kit.

*** IMPORTANT: Any product revisions or conversions must be made by the Manufacturer's Authorized Dealers, Distributors, or local service personnel.

† Measured at point of exit from dryer.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2008.

Printed in the U.S.A.

© Copyright 2012 Alliance Laundry Systems LLC

