

# Washer & Dryer Specifications

	Washers	Dryers
	SFNLCS, SFNLYS	Electric: SDELCFS, SDELYS Gas: SDGLCS, SDGLYS
<b>Basket/Cylinder Volume</b> - cu.ft. (liters)	2.84 (80)	7.0 (198)
<b>Width</b> - in (mm)	26 7/8" (683)	26 7/8" (683)
<b>Depth</b> - in (mm)	28" (711)	28" (711)
<b>Height*</b> - in (mm)	43" (1092)	43" (1092)
<b>Weight</b> - lb (kg)	250 (113)	Electric: 150 (68) Gas: 155 (70)
<b>Shipping Weight</b> - lb (kg)	270 (123)	Electric: 160 (73) Gas: 165 (75)
<b>Cycle Time</b> - minutes	27	45
<b>Motor HP</b> (Capacitor Start and Thermal Protected)	1, 750 W	1/3, 5.5 amps
<b>Water Consumption</b> - gal. per cycle	12.8	N/A
<b>Water Factor</b> - gal per cu. ft.	4.5	N/A
<b>Modified Energy Factor</b>	2.24	N/A
<b>Hot Water Usage</b> - gal per cycle	1.59	N/A
<b>Water Pressure</b> - psi (bar)	Pressure fill – 20 to 120 (1.4/8.3)	N/A
<b>Spin Speed</b> - RPM	500, 650, 1000	N/A
<b>Cycle/Temperature</b>	Normal Permanent Press Delicate Hot Warm Cold	High 160° Medium 155° Low 145° Delicate 115° No Heat
<b>Electrical Specifications and Circuit Requirements</b>	120/60/1-15 amp	Electric: 120/240/60/1-30 amp** Gas: 120/60/1-15 amp
<b>Motor</b>	Inverter Drive	60 Hz: 1725
<b>Btu per Hour</b>	N/A	25,000 (6300 kcal)
<b>Heating Element**</b>	N/A	5350 W, 240 V 4750 W, 208 V**
<b>Type of Gas</b> (Gas models only)	N/A	Factory-equipped natural/ mixed gas. Convertible to LP gas***
<b>Utility Connections</b> - in (mm)	N/A	Gas: 3/8" NPT (9,5)
<b>Air Outlet Diameter</b> - in (mm)	N/A	4" (102)
<b>Exhaust Airflow†</b> - cfm (liters/sec.)	N/A	220 (105)
<b>Maximum Exhaust Static Back Pressure</b>	N/A	0.6" W.C.
<b>Agency Approval</b>	cULus	Electric: cULus Gas: CSA Star
<b>Activation</b>	Coin/Card-Operated	Coin/Card-Operated
<b>Self-Adjusting Rear Legs</b>	No	No
<b>Cabinet Finish</b>	Stainless Steel	Stainless Steel
<b>Colors</b>	Stainless Steel	Stainless Steel
<b>Door Type</b>	Window	Window

\* Heights may vary slightly depending on leveling adjustments.

\*\* Factory equipped 120/240/60/1 - may be field converted to 120/208/60/1 by qualified servicer.

\*\*\* IMPORTANT: Any product revisions or conversions must be made by the Manufacturer's Authorized Dealers, Distributors, or local service personnel.

† Measured at point of exit from dryer.

At Speed Queen, we're so confident that our heavy-duty commercial washers and dryers are Commercial Built to Last Longer, that we're offering the following limited warranty to prove it: Through three years†† — Any part of the washer, dryer or stack dryer. Through five years†† — The washer transmission assembly, base and cabinet assembly including top, lid and door, against rust from inside out. Lifetime†† — The stainless steel washtub.

†† Parts only. Labor not included. See Speed Queen Warranty Bond for specifics.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2000.

©Copyright 2010 Alliance Laundry Systems LLC

