

	COIN PREP COIN PREP CARD	Top Load Washers	Single Load Dryers	Stack Dryers	Front Load Washers
		SWNLC2P, SWNLC2S SWNLX2S, SWNLX2P SWNLY2P, SWNLY2S	Elec, Gas SDELCRG, SDGLCRG Elec, Gas SDELXRG, SDGLXRG Elec, Gas SDELYRG, SDGLYRG	Elec, Gas SSELCF, SSGLCF Elec, Gas SSELXF, SSGLXF Elec, Gas SSELYF, SSGLYF	SFNNCR SFNNYR
Basket/Cylinder Volume - cu.ft. (liters)		3.26 (92.3)	7.0 (198)	7.0 (198)	2.84 (80)/7.0 (198)
Width - in (mm)		25 5/8" (651)	26 7/8" (683)	26 7/8" (683)	26 7/8" (683)
Depth - in (mm)		28" (711)	28" (711)	28" (711)	28" (711)
Height* - in (mm)		43" (1092)	43" (1092)	76 5/8" (1946)	43" (1092)
Weight - lb (kg)		190 (86)	Electric: 135 (61) Gas: 140 (64)	Electric: 265 (120) Gas: 275 (125)	240 (109)
Shipping Weight - lb (kg)		210 (95)	Electric: 145 (66) Gas: 150 (68)	Electric: 280 (127) Gas: 290 (132)	260 (118)
Cycle Time - minutes (default)		27	45	45	27/45
Motor HP (Capacitor Start and Thermal Protected)		1/2 HP, 375W	1/3 HP, 5.5 amps	1/3 HP, 5.5 amps	1 HP, 750 W
Water Consumption - gal (Liter)		27.3 (103.2)	N/A	N/A	11.0 (41.7)
Water Factor - gal/ft³ (Liters/Liter/cycle)		8.4 (1.12)	N/A	N/A	4.0 (0.53)
Modified Energy Factor - ft³/kWh/cycle (Liters/kWh/cycle)		1.75 (49.6)	N/A	N/A	2.40 (67.97)
Hot Water Usage - gal (Liter)		1.9 (7.4)	N/A	N/A	0.9 (3.3)
Water Pressure - psi (bar)		Pressure fill 20 to 120 (1.4/8.3)	N/A	N/A	Pressure fill 20 to 120 (1.4/8.3)
Spin Speed - RPM		473, 710	N/A	N/A	500, 650, 1000
Cycle/Temperature		Hot Warm Cold Normal Perm Press Delicate Delicate	High, Medium, Low, Delicate No Heat	High, Medium, Low, Delicate, No Heat	Hot Warm Cold Normal Perm Press Delicate Delicate
Electrical Specifications and Circuit Requirements		120/60/1-15 amp	Electric: 120/240/60/1 30 amp 120/208/60/1 30 amp Gas: 120-60/1-15 amp	Electric: 120/240/60/1 2 ea 30 amp 120/208/60/1 30 amp Gas: 2 ea 120-60/1-15 amp	120/60/1-15 amp
Btu per Hour (kcal)		N/A	25,000 (6300)	25,000 (6300)	N/A
Heating Element**		N/A	5350W, 240V 4750W, 208V	5350W, 240V 4750W, 208V	N/A
Type of Gas (Gas models only)		N/A	Factory-equipped natural/ mixed gas convertible to LP gas***	Factory-equipped natural/ mixed gas convertible to LP gas***	N/A
Utility Connections - in (mm)		N/A	Gas: 3/8" NPT (9.5)	Gas: 3/8" NPT (9.5)	N/A
Air Outlet Diameter - in (mm)		N/A	4" (102)	4" (102)	N/A
Exhaust Airflow† - cfm (liters/sec)		N/A	220 (105)	220 (105)	N/A
Maximum Exhaust Static Back Pressure		N/A	0.6" W.C.	0.6" W.C.	N/A
Agency Approval		cULus	Electric: cULus Gas: CSA Star	Electric: cULus Gas: CSA Star	cULus
Activation		Coin/Card Op	Coin/Card Op	Coin/Card Op	Coin/Card Op
Top and Lid Finish		Porcelain	Porcelain	N/A	Porcelain
Colors		White	White	White	White
Door Type		Window	Solid	Solid, Window	Window

* Heights may vary slightly depending on leveling adjustments.

** Electric dryers come equipped for 120/240/60/1 operation. They can be field converted to operate on 120/208/60/1 with optional 61928 conversion kit. Gas dryers can be field converted for operation on LP gas with optional 458P3 conversion kit.

*** IMPORTANT: Any product revisions or conversions must be made by the Manufacturer's Authorized Dealers, Distributors, or local service personnel.

† Measured at point of exit from dryer.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2008.

Printed in the U.S.A.

© Copyright 2012 Alliance Laundry Systems LLC

