

ON-PREMISES FRONTLOAD WASHER AND DRYER



FEATURES: Washer

- 6 factory presets with cycle modifiers that offer almost unlimited flexibility
- Time remaining countdown
- Low water usage
- Industry-leading 440 G-Force extraction
- Freestanding units can be installed on any floor and any level
- Suspension with out-of-balance logic
- Stainless steel cylinder
- Soap box with four compartments
- Door opens 180 degrees for easy loading and unloading
- Cycle modifier options include: Prewash and Second Rinse
- ADA certified

FEATURES: Dryer

- 6 drying programs
- Large door opening for easy loading and unloading
- Reversible door
- Front access to vital parts for easy maintenance
- Galvanized steel cylinder
- Nonremovable lint filter located in front for easy cleaning
- Powerful exhaust blower ensures short dry times and low operating costs
- Door opens 180 degrees for easy loading and unloading
- Electric or gas heating
- Time remaining countdown
- ADA certified



ERGONOMICAL
CONSTRUCTION



LARGE DOOR
OPENING



LOW WATER AND ENERGY
CONSUMPTION

| TYPE | | WASHER |
|------------------------------|-------|----------------|
| CAPACITY | lbs | 21.5 |
| CYLINDER VOLUME | cu ft | 3.42 |
| MOTOR | | |
| frequency controlled | Hp | .9 |
| EXTRACTION SPEED | rpm | 1200 |
| G-FORCE | | 440 |
| ELECTRICAL CONNECTION | | 120/60/1 |
| ELECTRIC HEATING | kW | 4.8 |
| DRAIN | | pump |
| WATER CONSUMPTION per cycle | g | 11.7 |
| WF (water factor) | | 3.8 |
| MEF (modified energy factor) | | 2.38 |
| DIMENSIONS | | |
| height | in | 40 7/16 |
| width | in | 26 7/8 |
| depth | in | 27 3/4 |
| shipping weight | lbs | 270 |
| net weight | lbs | 250 |
| shipping dimensions | | |
| height | in | 45 1/2 |
| width | in | 29 |
| depth | in | 32 3/4 |
| AGENCY APPROVALS | | cULus / cCSAus |

| TYPE | | DRYER |
|-----------------------|-------|---------------------------------------|
| CAPACITY | lbs | 18 |
| CYLINDER VOLUME | cu ft | 7 |
| ELECTRICAL CONNECTION | | 120/240/60/1 electric 120/60/1 gas |
| ELECTRIC HEATING | kW | 5.35 |
| GAS HEATING | BTU | 25,000 |
| MOTOR POWER | Hp | 1/3 |
| EXHAUST AIRFLOW | cfm | 220 |
| DIMENSIONS | | |
| height | in | 40 7/16 |
| width | in | 26 7/8 |
| depth | in | 28 |
| shipping weight | lbs | 160 |
| net weight | lbs | 150 |
| shipping dimensions | | |
| height | in | 45 1/2 |
| width | in | 29 |
| depth | in | 32 3/4 |
| AGENCY APPROVALS | | cULus / cCSAus |



(800) 688-0020 • info@bdslaundry.com

AY15-0018

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2008.

© 2015 Alliance Laundry Systems LLC

Alliance Laundry Systems LLC
Shepard Street
Ripon, WI 54971
1-800-553-5120

primus

laundry equipment