

VENDED SINGLE TUMBLE DRYER

50-75lb



FEATURES

- Easy-to-use microprocessor control
- Electric, gas, and steam heating
- Large door opening for easy loading and unloading
- Patented cylinder holes allow drywall screws to pass through without damage
- Galvanized cylinder
- Axial airflow
- Large self-cleaning lint screen
- Standard activation: single coin drop

OPTIONS

- Available activations include: dual coin drop, electronic drop, prep for coin, prep for card reader, and prep for central pay
- Reversing cylinder to avoid tangling of large items
- Stainless steel cylinder
- Stainless steel front panel



FAST DRYING
CYCLES



EASY OPERATION



LARGE DOOR
OPENING



(800) 688-0020 • info@bdslaundry.com

TYPE		PT50	PT75
CAPACITY			
capacity	lbs	50	75
cylinder volume	cu ft	18.6	22.4
cylinder diameter	in	37	37
AIRFLOW			
60 Hz	cfm	750	750
DRYING AVERAGE			
gas heating	lbs/min	1	1.36
electric heating	lbs/min	0.88	0.84
MOTOR			
fan	hp	0.5	0.75
drive	hp	0.5	0.75
ELECTRICAL CONNECTION			
gas and steam models		Non Rev Amps, (Rev Amps)	Non Rev Amps, (Rev Amps)
120/208-240/60/1 2W/3W+G		(12/6.5)	(13/7)
120/60/1 2W+G		9.3	13.8
200-208/240/60/1 2W+G		5.1/5.1	7.6/7.6
200-208/240/60/3 3W+G		2.8/2.8, (4.0/4.0)	3.8/3.8, (4.3/4.3)
380/60/3 3W+G		1.6, (2.0)	1.8, (2.1)
STEAM ONLY 440/60/3 3W+G		1.4, (1.9)	1.9, (2.1)
460-480/60/3 3W+G		1.4, (1.9)	1.9, (2.1)
electric models			
200-208/60/3 3W+G		89, (88)	89, (88)
240/60/3 3W+G		79, (78)	79, (78)
380/60/3 3W+G		47, (48)	47, (48)
440/60/3 3W+G		41, (41)	41, (41)
480/60/3 3W+G		38, (38)	38, (38)
GAS HEATING			
energy	kBTU/h	178	210.3
gas connection	NPT	.75"	.75"
STEAM HEATING			
high pressure 100psi	kBTU/h	178	210.3
steam connection	NPT	.75"	.75"
ELECTRIC HEATING			
energy	kW	30	30
EXHAUST			
	in	8	8
DIMENSIONS			
height	in	76.62	76.62
width	in	38.62	38.62
depth	in	48.25	54.25
net weight	lbs	545	615
shipping weight	lbs	602	677
shipping dimensions			
height	in	81	81
width	in	41.5	41.5
depth	in	52.1	56.4
AGENCY APPROVALS		cCSAUs	cCSAUs

AY15-0005

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2008.

© 2015 Alliance Laundry Systems LLC

Alliance Laundry Systems LLC
Shepard Street
Ripon, WI 54971
1-800-553-5120

primus

laundry equipment