

VENDED SINGLE TUMBLE DRYER

25, 30, 35, and 55lb



FEATURES

- Easy-to-use Microprocessor control
- Electric, gas, and steam heating
- Large door opening for easy loading and unloading
- Patented cylinder holes allow drywall screws to pass through without damage
- Galvanized cylinder
- Axial airflow
- Large self-cleaning lint screen
- Standard activation: single coin drop

OPTIONS

- Available activations include: dual coin drop, electronic drop, prep for coin, prep for card reader, and prep for central pay
- Reversing cylinder to avoid tangling of large items
- Stainless steel cylinder
- Stainless steel front panel



FAST DRYING
CYCLES



EASY OPERATION



SERVICE FRIENDLY



(800) 688-0020 • info@bdslaundry.com

TYPE		PT25	PT30	PT35	PT55
CAPACITY					
capacity	lbs	25	30	35	55
cylinder volume	cu ft	7.7	9.6	12.3	17.3
cylinder diameter	in	26.5	26.5	30	33
AIRFLOW					
60 Hz	cfm	500	500	650	700
DRYING AVERAGE					
gas heating	lbs/min	0.49	0.57	0.73	0.98
electric heating	lbs/min	0.38	0.6	0.74	0.88
MOTOR					
fan	hp	0.25	0.25	0.25	0.5
drive	hp	0.25	0.25	0.25	0.5
ELECTRICAL CONNECTION					
gas and steam models		Non Rev Amps, (Rev Amps)		Non Rev Amps, (Rev Amps)	
100/200-220/60/1 2W+G		11.0/5.8 (11.0/5.8)	11.0/5.8 (11.0/5.8)	11.0/5.8 (11.0/5.8)	9.8/4.9 (9.8/4.9)
120/208-240/60/1 2W/3W+G		12.0/6.7 (12.0/6.7)	12.0/6.7 (12.0/6.7)	12.0/6.7 (12.0/6.7)	9.2 /6.5 (9.2 /6.5)
200-208/240/60/3 3W+G		3.2/3.2 (4.0/4.0)	3.2/3.2 (4.0/4.0)	3.2/3.2 (4.0/4.0)	4.0/3.9 (4.0/4.5)
380/60/3 3W+G		1.5 (2.0)	1.5 (2.0)	1.5 (2.0)	-
460-480/60/3 3W+G		1.6 (2.0)	1.6 (2.0)	1.6 (2.0)	-
electric models					
208/60/1 3W+G		64	108	122	129
240/60/1 3W+G		57	94	107	115
200/60/1 2W+G		64	108	122	125
200-208/60/3 3W+G		37 (37)	62 (62)	71 (71)	79 (79)
240/60/3 3W+G		33 (33)	54 (54)	62 (62)	65 (65)
380/60/3 3W+G		20 (20)	33 (33)	38 (38)	-
460-480/60/3 3W+G		16 (16)	27 (27)	31 (31)	-
energy	kW	18.8	21.4	26.4	32.8
	kBTU/h	64	73	90	112
gas connection	NPT	.5"	.5"	.5"	.5"
STEAM HEATING					
high pressure 100psi	kW	39.6	39.6	48.6	-
	kBTU/h	135	135	166	-
steam connection	NPT	.75"	.75"	.75"	-
ELECTRIC HEATING					
energy	kW	12	21	24	27
EXHAUST					
	in	6	6	8	8
DIMENSIONS					
height	in	63.87	63.87	63.87	66.72
width	in	28	28	31.5	34.5
depth	in	46.87	46.87	46.87	53.62
net weight	lbs	299	331	361	435
shipping weight	lbs	332	364	394	476
shipping dimensions					
height	in	69	69	69	72
width	in	30	30	33	35.5
depth	in	43	49	49	59
AGENCY APPROVALS		cCSA _{US}	cCSA _{US}	cCSA _{US}	cCSA _{US}

AY15-0003

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2008.

© 2015 Alliance Laundry Systems LLC

Alliance Laundry Systems LLC
Shepard Street
Ripon, WI 54971
1-800-553-5120

primus

laundry equipment