

NOTABLE FEATURES




3-Point Serviceability:

Designed with improved serviceability in mind. Access points on console panel, front panel and toe panel simplify maintenance.



Inverter-Driven Motor:

Intelligent inverter measures performance, monitors motor limits and effectively balances load to ensure maximum water extraction during final spin.



Robust A-Frame Design:

Excellent strength and stability as a result of a heavy-duty, A-frame base constructed of channel iron.



Ergonomic Door Handle:

Rugged Easy Lock handle design boosts machine durability and provides a secure close.

ECOWASH COMMERCIAL WASHERS



Engineered with intelligence. Designed for versatility. Built to industrial-grade standards. All to deliver durable performance beyond the everyday.

EWR RIGID-MOUNT 200-G VENDED WASHER

RAPID-SPIN BASE MODEL NUMBERS

EWR-25M2 EWR-30M2
EWR-40M2 EWR-60M2

CHOOSE YOUR CONFIGURATION

MC2 = COIN
MR2 = CARD READY



Shown with MC2 Controller



See ADClaundry.com for full warranty details.

ADDITIONAL FEATURES

- **Full Stainless Steel Cabinet:** Protects against corrosion and enhances machine's longevity.
- **Coin or Card Ready:** Increased flexibility and enhanced revenue opportunities as a result of thoughtful payment engineering options—coin or card ready.
- **Hinged Control Panel:** Hinged, front-panel design allows convenient, easy access to internal components eliminating the need to remove the entire console when servicing.
- **Flexible Water Level Settings:** Helps to maximize water savings and customizes wash cycles for varied applications.

A pioneering history and a prolific future. ADC, a Whirlpool Corporation brand, creates innovative, performance-built equipment to handle the trials of daily commercial laundry use. Our reliable machines continue to prove why our name has a reputation for steadfast, innovative and versatile solutions the industry counts on.

RAPID-SPIN BASE MODELS	EWR-25M2	EWR-30M2	EWR-40M2	EWR-60M2
DRUM				
Load Capacity (lb/kg)	25 / 10	30 / 13	40 / 18	60 / 25
Drum Volume (cu. ft./liter)	3.5 / 100	4.6 / 130	6.4 / 181	8.7 / 247
Drum Diameter (in/mm)	24 3/8 / 620	24 3/8 / 620	27 1/2 / 700	30 3/8 / 770
Drum Depth (in/mm)	13 / 330	16 7/8 / 430	18 1/2 / 470	20 7/8 / 530
DIMENSIONS				
Width (in/mm)	28 1/4 / 719	28 1/4 / 719	31 / 788	34 3/4 / 884
Depth (cabinet) (in/mm)	25 5/8 / 645	31 1/8 / 791	31 1/2 / 800	38 / 965
Depth (overall) (in/mm)	28 5/8 / 727	34 1/2 / 876	35 1/8 / 892	40 1/2 / 1029
Height (in/mm)	45 5/8 / 1157	45 5/8 / 1157	51 1/2 / 1307	51 7/8 / 1319
Weight (lb/kg)	467 / 212	531 / 241	622 / 282	891 / 404
DIMENSIONS WITH PACKAGING				
Crated Width (in/mm)	31 1/2 / 800	31 1/2 / 800	34 3/4 / 883	37 3/4 / 959
Crated Depth (in/mm)	33 1/2 / 851	40 1/2 / 1029	40 1/2 / 1029	45 3/4 / 1162
Crated Height (in/mm)	54 3/4 / 1391	54 3/4 / 1391	60 3/4 / 1543	61 1/2 / 1562
Crated Weight (lb/kg)	517 / 235	581 / 264	678 / 308	964 / 438
DOOR				
Height to Bottom of Door	12 1/4 / 310	12 1/4 / 310	15 5/8 / 395	17 / 433
Door Opening Diameter (in/mm)	14 5/8 / 373	14 5/8 / 373	14 5/8 / 373	14 5/8 / 373
POWER				
Voltage / Phase (50hz or 60hz)	208-240 / 1, 3PH	208-240 / 1, 3PH	208-240 / 1, 3PH	208-240 / 1, 3PH
Full Load Current / Breaker (amps)—1PH	3.4 / 15	5.0 / 15	6.8 / 15	10.0 / 15
Full Load Current / Breaker (amps)—3PH	3.4 / 15	5.0 / 15	6.8 / 15	10.0 / 15
CONNECTIONS				
Water Inlet (GHT/BSP)	3/4" / 3/4"	3/4" / 3/4"	3/4" / 3/4"	3/4" / 3/4"
Steam Inlet (BSP)	1/2"	1/2"	1/2"	3/4"
Drain (in/mm)	3 / 76	3 / 76	3 / 76	3 / 76
CYLINDER SPEED				
Washing Speed (rpm)	50	50	47	45
Spinning Speed (rpm)	760	760	760	714
G-Force	200	200	200	200
WATER				
Average Usage (gallons)*	18.3	29	36.8	42.6

*One wash, two rinse cycles. No wash load.

Intuitive Micro Controls (IMC)

Our programmable microprocessor helps boost revenue through easy-to-use and customizable controls that offer cycle-based pricing. The versatile controls allow the modification of water levels and cycle times for each phase of the wash.



MC2 Controller—Coin



MR2 Controller—Card Ready