

# Premium Stack & Single Tumble Dryers

		STT30	STT45	ST050	ST075	
Control Option		Quantum Touch/Gold	Quantum Touch/Gold	Quantum Touch/Gold	Quantum Touch/Gold	
Capacity - lb (kg)		30 (14) x 2	45 (20) x 2	50 (23)	75 (34)	
Overall Width - in (mm)		31.5 (800)	34.5 (875)	38.5 (978)	38.5 (978)	
Overall Depth - in (mm)		42.8 (1087)	48.6 (1235)	46.8 (1189)	53.0 (1346)	
Overall Height - in (mm)		76.3 (1938)	81.3 (2065)	77.3 (1963)	77.3 (1963)	
Cylinder Diameter - in (mm)		30.0 (762)	33.0 (838)	37.0 (940)	37.0 (940)	
Cylinder Depth - in (mm)		26.0 (660)	30.0 (762)	30.0 (762)	36.0 (914)	
Cylinder Volume - cu. ft (liters)		10.6 (300)	14.8 (419)	18.7 (530)	22.4 (634)	
Reversing Cylinder		Standard	Standard	Standard	Standard	
Door Opening Size - in (mm)		22.6 (574)	26.9 (683)	26.9 (683)	26.9 (683)	
Heat Input Power		73,000 x 2 Btu/hr	95,000 x 2 Btu/hr	122,000 Btu/hr	150,000 Btu/hr	
Gas Connections - in (npt)		0.5	0.5	0.5	0.5	
Air Outlet - in (mm)		1 x 8 (200) oval	1 x 10 (250) oval	8 (203)	8 (200)	
Motor - HP	Fan	0.3	0.5	0.5	0.5	
	Cylinder	0.3	0.5	0.5	0.5	
Airflow - cfm		2 x 400	2 x 600	700	800	
Electrical Specs - amps	B	100-120V/50/60/1	16	-	9	12
	X	200-240V/50/60/1/3	9	12	6	7
Shipping Dimensions Approx. - in (mm)	Width	32.5 (826)	35.5 (902)	41.5 (1054)	41.5 (1054)	
	Depth	47.0 (1194)	54.0 (1372)	50.0 (1270)	56.0 (1422)	
	Height	79.9 (2029)	84.9 (2156)	81.0 (2057)	81.0 (2057)	
Net Weight - lb (kg)		570 (259)	710 (322)	660 (299)	690 (313)	
Shipping Weight - lb (kg)		600 (272)	750 (340)	710 (322)	740 (336)	
Agency Approvals		CSA	CSA	CSA	CSA	

# Premium Single Tumble Dryers

		ST030	ST035	ST055
Control Option		Quantum Touch/Gold	Quantum Touch/Gold	Quantum Touch/Gold
Capacity - lb (kg)		30 (14)	35 (16)	55 (25)
Overall Width - in (mm)		27.9 (709)	31.5 (800)	34.5 (876)
Overall Depth - in (mm)		45.5 (1156)	45.5 (1156)	53.1 (1349)
Overall Height - in (mm)		63.9 (1623)	63.9 (1623)	66.7 (1694)
Cylinder Diameter - in (mm)		26.5 (673)	30 (762)	33 (838)
Cylinder Depth - in (mm)		30.0 (762)	30.0 (762)	35.0 (889)
Cylinder Volume - cu. ft (liters)		9.6 (272)	12.3 (348)	17.3 (490)
Reversing Cylinder		Standard	Standard	Standard
Door Opening Size - in (mm)		22.7 (577)	22.7 (577)	26.9 (683)
Heat Input Power		73,000 Btu/hr	90,000 Btu/hr	112,000 Btu/hr
Gas Connections - in (npt)		0.5	0.5	0.5
Air Outlet - in (mm)		6 (152)	8 (200)	8 (200)
Motor - HP		Fan 0.3	0.3	0.5
		Cylinder 0.3	0.3	0.5
Airflow - cfm		500	600	700
Electrical Specs - amps	B	100-120V/50/60/1	10	12
	X	200-240V/50/60/1/3	6	7
Shipping Dimensions Approx. - in (mm)		Width	30.0 (762)	33.0 (838)
		Depth	49.0 (1245)	49.0 (1245)
		Height	67.6 (1717)	67.6 (1717)
Net Weight - lb (kg)		320 (145)	340 (154)	430 (195)
Shipping Weight - lb (kg)		340 (154)	360 (163)	470 (213)
Agency Approvals		CSA	CSA	CSA



(800) 688-0020 • info@bdslaundry.com

Tumble dryer models are made to suit a variety of electrical service characteristics. See your Speed Queen distributor for specifications. For further details on installation, refer to Installation, Operation and Maintenance instructions supplied with the tumble dryer. Amperage ratings available in Installation Manual. For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems of Alliance Laundry Systems are registered to ISO 9001.