

Commercial Washer Specifications

	Front Load Washer	Front Load Washer	Top Load Washer	Top Load Washer - Short Tub
Available Controls	Quantum	Quantum, E-Mech	Quantum, E-Mech	Quantum
Available Control Location	Front	Rear	Rear	Rear
Capacity - lb (kg)	21.5 (9.5)	21.5 (9.5)	16 (7.3)	14 (6.4)
Cylinder Volume - cu. Ft. (liters)	3.42 (96.8)	3.42 (96.8)	3.19 (90.3)	2.83 (80)
Width - in (mm)	26.875 (683)	26.875 (683)	25.63 (651)	25.63 (651)
Depth - in (mm)	27.73 (704)	27.73 (704)	28 (711)	28 (711)
Height - in (mm)	44.34 (1126)	43.875 (1114)	43.875 (1114)	43.875 (1114)
Spin Speed G-Force (RPM)	440 (1200)	440 (1200)	150 (710)	150 (710)
Motor Size - HP (kw)	Variable Speed Induction 0.9 (0.67)	Variable Speed Induction 0.9 (0.67)	0.5 (0.37)	0.5 (0.37)
Water Consumption per Cycle - g (l)**	13.68 (51.8)	13.68 (51.8)	28.07 (106)	24.9 (94.3)
IWF (Water Factor)**	4.0	4.0	8.8	8.8
IMEF (Modified Energy Factor)**	2.20	2.20	1.35	1.35
Available Water Temperatures	3	3	3	3
Available Cycles*	Normal, Perm Press, Delicate, Bulky	Normal, Perm Press, Delicate, Bulky	Normal, Perm Press, Delicate, Bulky	Normal, Perm Press, Delicate, Bulky
Water Pressure - PSI (Bar)	20-120 (1.4/8.3)	20-120 (1.4/8.3)	20-120 (1.4/8.3)	20-120 (1.4/8.3)
Cycle Indicator Lights	Yes	Yes	Yes	Yes
Cylinder Finish	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
Available Colors	White, Stainless	White	White	White
Door Type (Solid/Window)	Window	Window	-	-
Available Electrical Requirements - (Voltage/Hz/Ph - Circuit Amperage)	120/60/1 - 15 Amp	120/60/1 - 15 Amp	120/60/1 - 15 Amp	120/60/1 - 15 Amp
Net Weight - lb (kg)	260 (118)	260 (118)	218 (99)	218 (99)
Shipping Weight - lb (kg)	270 (122)	270 (122)	206 (93)	206 (93)
Shipping Width - in (mm)	30 (762)	30 (762)	28 (711)	28 (711)
Shipping Depth - in (mm)	34 (864)	34 (864)	30 (762)	30 (762)
Shipping Height - in (mm)	44.5 (1130)	44.5 (1130)	45 (1143)	45 (1143)
Available Agency Approvals	cULus	cULus	cULus	cULus



(800) 688-0020 • info@bdslaundry.com

ADA Compliant.

Note: Not all options are available for all models. Refer to the price list for the available models and options.

*Information shown applies to highest end control available.

**Average usage based on multiple load sizes and current DOE test protocol. Real usage will vary depending on load size, composition and cycle selectivity.

For further details on installation, refer to Installation, Operation and Maintenance instructions supplied with the tumble dryer. Amperage ratings available in Installation Manual. For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems of Alliance Laundry Systems are registered to ISO 9001.