

SMALL CHASSIS WASHERS & DRYERS

SPECIFICATIONS	FRONT LOAD WASHER	TOP LOAD WASHER	SINGLE DRYER	SINGLE DRYER	STACK DRYER/DRYER	STACK WASHER/DRYER
Models	UFNE5BJP115TW01	UWNMN2SP115CW01	UDEE5BGS173CW01 UDGE5BGS113TW01	UDEMNRGS173CW01 UDGMNRGS113CW01	USEMNAGS173TW01 USGMNAGS113TW01	UTEESASP175TW01 UTGE5ASP115TW01 UTEESASP285CW01
Available Controls	Electronic	Emech	Electronic	Emech	Emech	Electronic
Available Control Location	Front	Rear	Front	Rear	Front	Front
Capacity - lb (kg)	21.5 (9.5)	16 (7.3)	18 (8.2)	18 (8.2)	18 (8.2)	See front control front load washer and dryer specs to the left
Cylinder Volume - cu. Ft. (liters)	3.42 (96.8)	3.19 (90.3)	7.0 (198)	7.0 (198)	7.0 (198)	
Width - in (mm)	26 7/8 (683)	25 5/8 (650)	26 7/8 (683)	26 7/8 (683)	26 7/8 (683)	26 7/8 (683)
Depth - in (mm)	27 3/4 (704)	28 (711)	28 (711)	28 (711)	29 (737)	27 3/4 (704)
Height - in (mm)	40 7/16 (1027)	43 (1092)	40 7/16 (1027)	43 (1092)	78 3/16 (1986)	78 3/16 (1986)
Spin Speed - G-Force (RPM)	440 (1200)	150 (710)	N/A	N/A	N/A	See front control front load washer and dryer specs to the left.
Motor Size - HP (kw)	Variable Speed Induction 0.9 (0.67)	1/2 (0.37)	1/3 (0.25)	1/3 (0.25)	1/3 (0.25)	
Water Consumption per Cycle - g (l)	13.68 (51.8)	28.07 (106)	N/A	N/A	N/A	
IWF (Water Factor)	4.0	8.8	N/A	N/A	N/A	
IMEF (Modified Energy Factor)	2.20	1.35	N/A	N/A	N/A	
Available Heat Sources	N/A	N/A	Gas or Electric	Gas or Electric	Gas or Electric	
Available Heating Element (Electric W)	N/A	N/A	5350 @ 240V	5350 @ 240V	5350 @ 240V	
Gas Inlet Connection - in (mm)	N/A	N/A	3/8 (9.5)	3/8 (9.5)	3/8 (9.5)	
Gas Consumption - BTU/Hr	N/A	N/A	22,500	22,500	22,500	
Exhaust Outlet Diameter - in (mm)	N/A	N/A	4 (102)	4 (102)	4 (102)	
Exhaust Airflow - cfm (liters/sec)	N/A	N/A	220 (105)	220 (105)	220 (105)	
Available Water Temperatures	3	3	N/A	N/A	N/A	
Available Cycles	Heavy Duty, Normal Eco, Perm Press, Delicate, Rinse & Spin, Spin Only	Normal, Perm Press, Delicate	Regular, Perm Press, Delicate, Time Dry, Quick Dry, Fluff Up	Normal, Perm Press, Delicate, No Heat	Normal, Perm Press, Delicate, No Heat	
Water Pressure - PSI (Bar)	20-120 (1.4/8.3)	20-120 (1.4/8.3)	N/A	N/A	N/A	
Cycle Indicator Lights	Yes	Yes	Yes	Yes	Yes	
Cylinder Finish	Stainless Steel	Stainless Steel	Galvanized	Galvanized	Galvanized	
Available Colors	White	White	White	White	White	White
Door Type (Solid/Window)	Window	N/A	Solid	Solid	Solid	Window
Available Electrical Requirements - (Voltage/Hz/Ph)	120/60/1 - 15 Amp	120/60/1 - 15 Amp	Gas: 120/60/1 - 15 Amp Electric: 120/240/60/1 - 30 Amp	Gas: 120/60/1 - 15 Amp Electric: 120/240/60/1 - 30 Amp	Gas: 120/60/1 - 15 Amp Electric: 120/240/60/1 - 30 Amp	See front control front load washer and dryer specs to the left. For Canada Market, only a single electrical cord is provided requiring 120/240/50-60/1ph 40 Amp
Net Weight - lb (kg)	260 (118)	190 (86)	Elec/Gas 145/150 (66/68)	Elec/Gas 135/140 (61/64)	Elec/Gas 265/275 (120/125)	390 (177)
Shipping Weight - lb (kg)	270 (122)	210 (95)	Elec/Gas 155/160 (70/73)	Elec/Gas 145/150 (66/68)	Elec/Gas 280/290 (127/132)	425 (193)
Shipping Width - in (mm)	30 (762)	27 1/2 (699)	29 (737)	29 (737)	29 (737)	29 (737)
Shipping Depth - in (mm)	34 (864)	30 (762)	32 3/4 (832)	32 3/4 (832)	32 3/4 (832)	32 3/4 (832)
Shipping Height - in (mm)	45 1/2 (1156)	44 1/4 (1124)	45 1/2 (1156)	45 1/2 (1156)	80 (2032)	80 (2032)
ADA Compliant	Yes	No	Yes	Yes	No	No
Available Agency Approvals	cULUS	cULUS	Elec: cULUS, Gas: cCSAUS	Elec: cULUS, Gas: cCSAUS	Elec: cULUS, Gas: cCSAUS	Elec: cULUS, Gas: cCSAUS

Note: Not all options are available for all models. Refer to the price list for the available models and options.

** For Canada Market Stack Dryer / Dyer and Stack Washer / Dryer not available with gas.

TO LEARN MORE OR TO FIND A DISTRIBUTOR IN YOUR AREA, VISIT UNIMAC.COM
ALLIANCE LAUNDRY SYSTEMS - SHEPARD ST, RIPON, WI 54971 - 1.800.587.5458



(800) 688-0020 · info@bdslaundry.com

Consult your UniMac distributor for details. For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems at Alliance Laundry Systems are registered to ISO 9001.