

# CLASSIC SINGLE AND STACK TUMBLE DRYERS

SPECIFICATIONS		UT25	UT30	UTT30	UTT45	
Control Options		M Series, DDT	M Series, DDT	M Series, DDT	M Series, DDT	
Capacity - lb (kg)		25 (11)	30 (14)	30 (14)	45 (20)	
Overall Width - in (mm)		28 (711)	28 (711)	31.5 (800)	34.5 (875)	
Overall Depth - in (mm)		40.9 (1038)	46.9 (1191)	42.9 (1086)	48.6 (1235)	
Overall Height - in (mm)		63.9 (1625)	63.9 (1625)	76.25 (1937)	81.25 (2064)	
Cylinder Diameter - in (mm)		26.5 (673)	26.5 (673)	30 (762)	33 (838)	
Cylinder Depth - in (mm)		24 (610)	30 (762)	26 (660)	30 (762)	
Cylinder Volume - cu ft (liters)		7.7 (220)	9.6 (270)	10.6 (300)	14.8 (420)	
Reversing Cylinder		Option	Option	N/A	N/A	
Door Opening Size		22.7 (576)	22.7 (576)	22.6 (575)	22.9 (581)	
Water Inlet Size (C.A.R.E.™ System)		-	-	-	-	
Energy Data		Gas 64,000 Btu/hr Electric 12 kW	73,000 Btu/hr 21 kW	73,000 x 2 Btu/hr 21 x 2 kW	95,000 x 2 Btu/hr -	
Gas Connections - in (npt)		0.5	0.5	0.5	0.5	
Air Outlet - in (mm)		6 (152)	6 (152)	1 x 8 (200)	1 x 10 (250)	
Motor - HP		Fan 0.25 Cylinder 0.25	0.25 0.25	0.5 0.5	0.5 0.5	
Airflow - cfm		50 Hz 430 (203) 60 Hz 500 (236)	430 (203) 500 (236)	340 (160) 400 (189)	500 (236) 600 (283)	
Electrical Specs - amps		Gas Models A2 100/200-220V/60/1 11/5.8 B2 120/208-240V/60/1 12/6.7 F6 200-208/240V/60/3 3.2/3.2 Q1 460-480V/60/3 1.6 A1 100/200V/50/1 12.1/7.5 J2 230-240V/50/1 7.5 M2 380/400-415V/50/3 1.5/1.6 G2 208-240V/60/1 - Electric Models F5 200-208V/60/3 37 J8 240V/60/3 33 Q1 460-480V/60/3 16 J2 230-240V/50/1 58 M1 380V/50/3 20 N1 400-415V/50/3 18	11/5.8 12/6.7 3.2/3.2 1.6 12.1/7.5 7.5 1.5/1.6 - 62 54 27 95 33 31	11/5.8 12/6.7 3.2/3.2 1.6 12.1/7.5 7.5 1.5/1.6 - 62 54 27 95 33 31	22/11.6 16/8.0 6.4/6.4 3.3 24.2/15.0 15.0 - - 62 x 2 - - - 33 x 2 31 x 2	- - 9.6/9.6 - - - 12.0 - - - - - -
Shipping Dimensions Approx. - in (mm)		Width 30 (760) Depth 43 (1090) Height 67.6 (1720)	30 (760) 49 (1240) 67.6 (1720)	32.5 (830) 47 (1190) 79.9 (2030)	35.5 (900) 54 (1370) 84.9 (2160)	
Net Weight - lb (kg)		300 (137)	330 (150)	544 (247)	673 (305)	
Shipping Weight - lb (kg)		332 (151)	364 (165)	582 (264)	718 (326)	
Agency Approvals		CSA	CSA	CSA	CSA	

# CLASSIC SINGLE TUMBLE DRYERS

SPECIFICATIONS		UT50	UT55	UT75
Control Options		M Series, DDT	M Series, DDT	M Series, DDT
Capacity - lb (kg)		50 (23)	55 (25)	75 (34)
Overall Width - in (mm)		38.6 (981)	34.5 (876)	38.6 (981)
Overall Depth - in (mm)		46.25 (1226)	53.6 (1365)	54.25 (1378)
Overall Height - in (mm)		76.6 (1946)	66.75 (1695)	76.6 (1946)
Cylinder Diameter - in (mm)		37 (940)	33 (838)	37 (940)
Cylinder Depth - in (mm)		30 (762)	35 (889)	36 (914)
Cylinder Volume - cu ft (liters)		18.6 (528)	17.3 (490)	22.4 (634)
Reversing Cylinder		Option	Option	Option
Door Opening Size - in (mm)		26.9 (683)	26.9 (683)	26.9 (683)
Water Inlet Size (C.A.R.E.™ System)		(1) 3/4"-11 1/2" NH Hose Connection	-	(1) 3/4"-11 1/2" NH Hose Connection
Energy Data		Gas 130,000 Btu/hr Steam 178,000 Btu/hr Electric 30 kW	112,000 Btu/hr - 27 kW	165,000 Btu/hr 210,300 Btu/hr 30 kW
Gas Connections - in (npt)		0.5	0.5	0.5
Air Outlet - in (mm)		8 (200)	8 (200)	8 (200)
Motor - HP		Fan 0.5 Cylinder 0.5	0.5 0.5	0.75 0.75
Airflow - cfm		50 Hz 750 (354) 60 Hz	600 (283) 700 (330)	750 (354) 920 (434)
Electrical Specs - amps		Gas and Steam NonRev/Rev		NonRev/Rev
<b>A2</b>	100/200-220V/60/1	-	9.8/4.9	-
<b>B1</b>	120V/60/1	9.3/12.6	-	13.8/13.0
<b>B2</b>	120/208-240V/60/1	-	9.2/6.5	-
<b>F3</b>	200-208/240V/60/1	5.1/6.5	-	7.6/7.0
<b>F6</b>	200-208/240V/60/3	2.8/4.0	4.0/3.9	3.8/4.3
<b>Q1</b>	460-480V/60/3	1.4/1.9	-	1.9/2.1
<b>J2</b>	230-240V/50/1	6.3/6.9	-	6.7/7.0
<b>M2</b>	380/400-415V/50/3	1.6/2.0	-	1.8/2.1
	Electric			
<b>F5</b>	200-208V/60/3	89/88	79	89/88
<b>Q2</b>	480V/60/3	38/38	-	38/38
<b>M1</b>	380V/50/3	47/48	-	47/48
<b>N1</b>	400-415V/50/3	43/44	-	43/44
Shipping Dimensions Approx - in (mm)		Width 41.5 (1050) Depth 50 (1270) Height Gas & Electric - 81(2060) Steam - 83.5 (2120)	33 (840) 49 (1240) 67.6 (1720)	41.5 (1050) 56 (1420) Gas & Electric - 81 (2060) Steam - 83.5 (2120)
Net Weight - lb (kg)		545 (247)	435 (197)	615 (279)
Shipping Weight - lb (kg)		602 (273)	476 (216)	677 (307)
Agency Approvals		CSA	CSA	CSA