



**OUR UNILINC™  
CONTROLS ARE  
REVOLUTIONIZING THE  
WAY PEOPLE THINK  
ABOUT LAUNDRY**

- **SAVE WATER AND ENERGY**
- **INCREASE THROUGHPUT**
- **GAIN FLEXIBILITY AND CONTROL**
- **MONITOR YOUR LAUNDRY**
- **EASY TO USE**
- **WIRELESS NETWORKING**
- **48 PROGRAMMABLE CYCLES**



**UW HARDMOUNT  
WASHER-EXTRACTORS 45 AND 65LB**

SPECIFICATIONS		UW45		UW65			
Control Options		UniLinc™		UniLinc™			
Capacity - lb (kg)		45 (20)		65 (30)			
Cylinder Diameter - in (mm)		31 (787)		31 (787)			
Cylinder Depth - in (mm)		16.6 (422)		22.1 (561)			
Cylinder Volume - cu ft (liters)		7.3 (207)		9.7 (275)			
Height - in (mm)		64.7 (1643)		64.7 (1643)			
Width - in (mm)		34.1 (866)		34.1 (866)			
Depth - in (mm)		45.3 (1151)		51.1 (1298)			
Door Opening Size - in (mm)		17.8 (452)		17.8 (452)			
Door Bottom to Floor - in (mm)		28.8 (732)		28.8 (732)			
Motor Size - HP (kW)		5 (3.7)		5 (3.7)			
Total # of Speeds		L Sp	V Sp	L Sp	M Sp	V Sp	
		5	9	5	6	9	
*Cylinder Speed RPM ( G-Force)		Gentle	30 (0.4)	30 (0.4)	30 (0.4)	30 (0.4)	
		Wash	42 (0.78)	42 (0.78)	42 (0.78)	42 (0.78)	42 (0.78)
		Distribution	75 (2.5)	75 (2.5)	75 (2.5)	75 (2.5)	75 (2.5)
		Very Low	248 (27)	248 (27)	248 (27)	248 (27)	248 (27)
		Low	477 (100)	477 (100)	477 (100)	477 (100)	477 (100)
		Medium	—	674 (200)	—	674 (200)	674 (200)
		High	—	754 (250)	—	—	754 (250)
		Very High	—	826 (300)	—	—	826 (300)
Ultra High	—	954 (400)	—	—	954 (400)		
Drain Diameter - in (mm)		3 (76)		3 (76)			
Steam Connection - in (mm)		½ (13)		½ (13)			
Water Inlet Connection - in (mm)		4 @ ¾ (19)		4 @ ¾ (19)			
Shipping Dimensions - in (mm)		Width	37.2 (945)		37.2 (945)		
		Depth	53.8 (1370)		53.8 (1370)		
		Height	65 (1650)		65 (1650)		
Net Weight - lb (kg)		1080 (490)		1110 (499)			
Standard Shipping Weight - lb (kg)		1120 (508)		1150 (522)			
Slat Crate Shipping Weight - lb (kg)		1250 (567)		1280 (581)			
Agency Approvals		cULus		cULus			

\*All RPM and G-Force results are reliant upon wash load composition and incoming voltage.

**TO LEARN MORE OR TO FIND A DISTRIBUTOR IN YOUR AREA, VISIT UNIMAC.COM  
ALLIANCE LAUNDRY SYSTEMS - SHEPARD ST, RIPON, WI 54971 - 1.800.587.5458**

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems at Alliance Laundry Systems is registered to ISO 9001.



(800) 688-0020 • info@bdslaundry.com

# UW HARDMOUNT WASHER-EXTRACTORS 85-200LB

SPECIFICATIONS		UW85	UW105	UW130	UW160	UW200
Capacity - lb (kg)		85 (38.5)	105 (47.6)	130 (60)	160 (72.6)	200 (90.7)
Cylinder Diameter - in (mm)		36 (914)	36 (914)	42 (1067)	42 (1067)	42 (1067)
Cylinder Depth - in (mm)		22 (559)	27 (686)	24½ (622)	30 (762)	37½ (953)
Cylinder Volume - cu ft (liters)		13 (368)	15.9 (450)	19.6 (555)	24.1 (682)	30.1 (852)
Width - in (mm)		40.1 (1019)	40.1 (1019)	46.1 (1171)	46.1 (1171)	46.1 (1171)
Depth - in (mm)		51.2 (1300)	56.2 (1427)	54.5 (1384)	60 (1524)	67.5 (1715)
Height - in (mm)		67.6 (1717)	67.6 (1717)	72.6 (1844)	72.6 (1844)	72.6 (1844)
Door Opening Size - in (mm)		21 (533)	21 (533)	24 <sup>13</sup> / <sub>16</sub> (630)	24 <sup>13</sup> / <sub>16</sub> (630)	24 <sup>13</sup> / <sub>16</sub> (630)
Door Bottom to Floor - in (mm)		28.8 (732)	28.8 (732)	30.5 (775)	30.5 (775)	30.5 (775)
Motor Size - HP (kW)		7.5 (5.6)	7.5 (5.6)	10 (7.5)	10 (7.5)	10 (7.5)
Control Options		UniLinc™	UniLinc™	UniLinc™	UniLinc™	UniLinc™
Total # of Speeds		V Sp	V Sp	V Sp	V Sp	M Sp
		9	9	9	9	9
Cylinder Speed RPM ( G-Force)	Gentle	28 (.40)	28 (.40)	26 (.40)	26 (.40)	26 (.40)
	Wash	39 (.78)	39 (.78)	36 (.77)	36 (.77)	36 (.77)
	Distribution	70 (2.5)	70 (2.5)	65 (2.5)	65 (2.5)	65 (2.5)
	Very Low Extract	230 (27)	230 (27)	213 (27)	213 (27)	213 (27)
	Low Extract	443 (100)	443 (100)	410 (100)	410 (100)	366 (80)
	Medium	542 (150)	542 (150)	502 (150)	502 (150)	410 (100)
	High Extract	626 (200)	626 (200)	579 (200)	579 (200)	458 (125)
	Very High Extract	700 (250)	700 (250)	648 (250)	648 (250)	502 (150)
Ultra High Extract	766 (300)	766 (300)	710 (300)	710 (300)	579 (200)	
Drain Diameter - in (mm)		2 @ 3 (76)	2 @ 3 (76)	2 @ 3 (76)	2 @ 3 (76)	2 @ 3 (76)
Steam Connection - in (mm)		½ (13)	½ (13)	¾ (19)	¾ (19)	¾ (19)
Water Inlet Connection - in (mm)		4 @ ¾ (19)	4 @ ¾ (19)	2 @ 1 (25) + 2 @ ¾ (19)	2 @ 1 (25) + 2 @ ¾ (19)	2 @ 1 (25) + 2 @ ¾ (19)
Shipping Dimensions - in (mm)	Width	43.2 (1097)	43.2 (1097)	49.2 (1250)	49.2 (1250)	49.2 (1250)
	Depth	61.8 (1570)	61.8 (1570)	64.8 (1646)	64.8 (1646)	72.3 (1836)
	Height	69.4 (1763)	69.4 (1763)	76.4 (1941)	76.4 (1941)	76.4 (1941)
Net Weight - lb (kg)		1670 (757)	1700 (771)	2040 (925)	2070 (939)	2160 (980)
Standard Shipping Weight - lb (kg)		1720 (780)	1750 (794)	2100 (953)	2130 (966)	2220 (1007)
Slat Crate Shipping Weight - lb (kg)		1870 (848)	1900 (862)	2260 (1025)	2290 (1039)	2390 (1084)
Agency Approvals		cULus	cULus	cULus	cULus	cULus

**TO LEARN MORE OR TO FIND A DISTRIBUTOR IN YOUR AREA, VISIT UNIMAC.COM  
ALLIANCE LAUNDRY SYSTEMS - SHEPARD ST, RIPON, WI 54971 - 1.800.587.5458**

Consult your UniMac distributor for details. For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems at Alliance Laundry Systems' Ripon facility have been registered to ISO 9001:2008.



(800) 688-0020 • info@bdslaundry.com