

UW HARDMOUNT WASHER-EXTRACTORS 45-130LB

SPECIFICATIONS		UW45		UW65		UW85	UW105	UW130	
Capacity - lb (kg)		45 (20.4)		65 (30)		85 (38.5)	105 (47.6)	130 (60)	
Cylinder Diameter - in (mm)		31 (787)		31 (787)		36 (914)	36 (914)	42 (1067)	
Cylinder Depth - in (mm)		16.6 (422)		22.1 (561)		22 (559)	27 (686)	24½ (630)	
Cylinder Volume - cu ft (liters)		7.3 (207)		9.7 (275)		13 (368)	15.9 (450)	19.6 (555)	
Width - in (mm)		34.1 (866)		34.1 (866)		40.1 (1019)	40.1 (1019)	46.1 (1171)	
Depth - in (mm)		45.3 (1151)		51.1 (1298)		51.2 (1300)	56.2 (1427)	54.5 (1384)	
Height - in (mm)		64.7 (1643)		64.7 (1643)		67.6 (1717)	67.6 (1717)	72.6 (1844)	
Door Opening Size - in (mm)		17.8 (452)		17.8 (452)		21 (533)	21 (533)	24 ¹ / ₁₆ (630)	
Door Bottom to Floor - in (mm)		28.08 (713.23)		28.08 (713.23)		28.8 (732)	28.8 (732)	30.5 (775)	
Motor Size - HP (kW)		5 (3.7)		5 (3.7)		7.5 (5.6)	7.5 (5.6)	10 (7.5)	
Control Options		M30		M30		M30	M30	M30	
Total # of Speeds		L Sp	M Sp	L Sp	M Sp	M Sp	M Sp	M Sp	
		5	6	5	6	7	7	7	
Cylinder Speed RPM (G-Force)		Gentle	30 (0.4)	30 (0.4)	30 (0.4)	30 (0.4)	28 (.40)	26 (.40)	
		Wash	42 (0.78)	42 (0.78)	42 (0.78)	42 (0.78)	39 (.78)	36 (.77)	
		Distribution	75 (2.5)	75 (2.5)	75 (2.5)	75 (2.5)	70 (2.5)	70 (2.5)	65 (2.5)
		Very Low Extract	248 (27)	248 (27)	248 (27)	248 (27)	230 (27)	230 (27)	213 (27)
		Low Extract	477 (100)	477 (100)	477 (100)	477 (100)	443 (100)	443 (100)	410 (100)
		Medium	-	674 (200)	-	674 (200)	542 (150)	542 (150)	502 (150)
		High	-	-	-	-	626 (200)	626 (200)	579 (200)
Drain Diameter - in (mm)		3 (76)		3 (76)		3 (76)	3 (76)	3 (76)	
Steam Connection - in (mm)		½ (13)		½ (13)		½ (13)	½ (13)	¾ (19)	
Water Inlet Connection - in (mm)		2 @ ¾ (19)		2 @ ¾ (19)		2 @ ¾ (19)	2 @ ¾ (19)	2 @ 1 (25)	
Shipping Dimensions - in (mm)		Width	37.2 (945)		37.2 (945)		43.2 (1097)	43.2 (1097)	49.2 (1250)
		Depth	53.8 (1367)		53.8 (1367)		61.8 (1570)	61.8 (1570)	64.8 (1646)
		Height	65 (1651)		65 (1651)		69.4 (1763)	69.4 (1763)	76.4 (1941)
Net Weight - lb (kg)		1080 (490)		1110 (503)		1670 (757)	1700 (771)	2040 (925)	
Standard Shipping Weight - lb (kg)		1120 (508)		1150 (522)		1720 (780)	1750 (794)	2100 (953)	
Slat Crate Shipping Weight - lb (kg)		1250 (567)		1280 (581)		1870 (848)	1900 (862)	2260 (1025)	
Agency Approvals		cULus		cULus		cULus	cULus	cULus	

**TO LEARN MORE OR TO FIND A DISTRIBUTOR IN YOUR AREA, VISIT UNIMAC.COM
ALLIANCE LAUNDRY SYSTEMS - SHEPARD ST, RIPON, WI 54971 - 1.800.587.5458**

Consult your UniMac distributor for details. For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems at Alliance Laundry Systems are registered to ISO 9001.



(800) 688-0020 • info@bdslaundry.com