


MODELS	I10	FCU13X66	FCU13X82	FCU20X79	FCU20X102	FCU20X126	
Roll Diameter - in (mm)	10 (254)	13 (320)	13 (320)	20 (502)	20 (502)	20 (502)	
Finishing Width - in (mm)	55 (1400)	66 (1664)	82 (2080)	79 (2000)	102 (2600)	126 (3200)	
Ironing Speed - ft/m (m/m)	7-13 (2-4)	3-20 (1-6)	3-20 (1-6)	5-26 (1.5-8)	5-26 (1.5-8)	5-26 (1.5-8)	
IRONER DIMENSIONS (WORKING POSITION)							
Width - in (mm)	70 7/8 (1800)	86 1/2 (2194)	102 3/4 (2610)	108 1/4 (2750)	132 (3350)	155 1/2 (3950)	
Depth - in (mm)	16 1/2 (420)	30 (765)	30 (765)	41 1/2 (1052)	42 3/4 (1087)	42 3/4 (1087)	
Height - in (mm)	39 5/8 (1005)	43 3/4 (1110)	43 3/4 (1110)	48 1/2 (1232)	48 1/2 (1232)	48 1/2 (1232)	
Roll Motor - HP (kW)	0.29 (0.215)	.24 (.18)	.24 (.18)	.50 (.37)	.50 (.37)	.50 (.37)	
Roll Exhaust Motor - HP (kW)	N/A	0.17 (0.125)	0.17 (0.125)	0.34 (0.255)	0.34 (2 x 0.255)	0.34 (2 x 0.255)	
Roll Exhaust Duct - in (mm)	2.17 (55)	6 (150)	6 (150)	6 (150)	6 (2 x 150)	6 (2 x 150)	
ELECTRIC HEATING							
E heat input power - HP (kW)	11.3 (8.4)	32.6 (24.3)	37.4 (27.9)	49.9 (37.2)	72.4 (54.0)	86.9 (64.8)	
Electrical Requirements • Circuit Breaker	230/60/3 • 25	230/60/3 • 80	230/60/3 • 80				
GAS HEATING							
Maximum Gas Input - Btu (kW)	N/A	85,303 (25)	102,364 (30)	122,837 (36)	177,431 (52)	225,201 (66)	
Gas Inlet - in (mm)	N/A	3/4 (19)	3/4 (19)	3/4 (19)	3/4 (19)	3/4 (19)	
Electrical Requirements • Circuit Breaker	N/A	120/60/1 • 15	120/60/1 • 15	230/60/3 • 15	230/60/3 • 15	230/60/3 • 15	
SHIPPING DIMENSIONS							
Height - in (mm)	45 1/4 (1150)	49 5/8 (1260)	49 5/8 (1260)	59 (1550)	59 (1550)	59 (1550)	
Width - in (mm)	74 (1880)	86 1/4 (2190)	102 3/4 (2610)	113 1/2 (2885)	137 1/4 (3485)	160 3/4 (4085)	
Depth - in (mm)	19 11/16 (500)	31 1/2 (800)	31 1/2 (800)	43 (1095)	43 (1095)	43 (1095)	
Weight - lb (kg)	Electric	328 (149)	1069 (485)	1235 (560)	2833 (1285)	3483 (1580)	4034 (1830)
	Gas	N/A	1025 (465)	1191 (540)	3120 (1415)	3549 (1610)	4299 (1950)
Net Weight - lb (kg)	Electric	287 (130)	959 (435)	1080 (490)	2249 (1020)	2778 (1260)	3241 (1470)
	Gas	N/A	904 (410)	1025 (465)	2535 (1150)	2844 (1290)	3505 (1590)
Approvals	ETL	CSA	CSA	CSA	CSA	CSA	

Electric heated models not available in Canada.



To learn more, or to find a distributor in your area, visit UNIMAC.COM
Alliance Laundry Systems - Shepard St, Ripon WI 54971 - 1.800.587.5458

Consult your UniMac distributor for more details. For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications are subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2008.

© 2017 Alliance Laundry Systems. Printed in the U.S.A.



(800) 688-0020 • info@bdslaundry.com



by Alliance Laundry Systems

AU18-0009