

# PREMIUM SINGLE AND STACK TUMBLE DRYERS

SPECIFICATIONS		UT030	UT035	UTT30	UTT45
Control Options		UniLinc	UniLinc, M Series	UniLinc	UniLinc
Capacity - lb (kg)		30 (13)	35 (16)	30 (13) x 2	45 (20) x 2
Overall Width - in (mm)		27.9 (710)	31.5 (800)	31.5 (800)	34.5 (875)
Overall Depth - in (mm)		45.5 (1155)	45.5 (1155)	42.8 (1090)	48.6 (1235)
Overall Height - in (mm)		63.9 (1625)	63.9 (1625)	76.3 (1940)	81.3 (2065)
Cylinder Diameter - in (mm)		26.5 (673)	30 (762)	30.0 (762)	33.0 (838)
Cylinder Depth - in (mm)		30.0 (762)	30.0 (762)	26.0 (660)	30.0 (762)
Cylinder Volume - cu ft (liters)		9.6 (270)	12.3 (350)	10.6 (300)	14.8 (420)
Reversing Cylinder		Option	Option	Option	Option
Door Opening Size		22.7 (577)	22.7 (577)	22.6 (574)	26.9 (683)
Heat Input Power		Gas 73,000 Btu/hr Steam 83,514 Btu/hr Electric 21 kW	90,000 Btu/hr 103,440 Btu/hr 24 kW	73,000 x 2 Btu/hr 85,442 x 2 Btu/hr 21 x 2 kW	95,000 x 2 Btu/hr - -
Gas Connections - in (npt)		0.5	0.5	0.5	0.5
Plumbing Connections - Steam - in (npt)		0.75	0.75	0.75	-
Air Outlet - in (mm)		6 (152)	8 (200)	1 x 8 (200) Oval	1 x 10 (250) Oval
Motor - HP		Fan 0.5 Cylinder 0.3	0.5 0.3	0.5 0.3	0.5 0.5
Airflow - cfm (liters/sec)		600	600	2 x 400	2 x 600
Electrical Specs - amps		Gas Models 100-120V/50-60/1 10 200-240V/50-60/1-3 6 440-480V/50-60/3 3 200-240/50-60/3 - Electric Models 200-208V/50-60/1 104 230-240V/50-60/1 90 200-208V/50-60/3 61 230-240V/50-60/3 52 440V/50-60/3 29 460-480V/50-60/3 27	10 6 3 - 118 102 69 59 32 30	16 9 6 - - 61 x 2 52 x 2 29 x 2 27 x 2	- 12 6 - - - - -
Shipping Dimensions Approx. - in (mm)		Width 30.0 (762) Depth 49.0 (1245) Height 67.6 (1717)	33.0 (838) 49.0 (1245) 67.6 (1717)	32.5 (826) 47.0 (1194) 79.9 (2029)	35.5 (902) 54.0 (1372) 84.9 (2156)
Net Weight - lb (kg)		Gas & Steam 320 (145) Electric 330 (150)	340 (155) 350 (160)	570 (260) / 610 (275) 660 (300)	710 (320) -
Shipping Weight - lb (kg)		Gas & Steam 340 (155) Electric 350 (160)	360 (165) 370 (170)	600 (270) / 640 (290) 690 (313)	750 (340) -
Agency Approvals		CSA	CSA	CSA	CSA



(800) 688-0020 · info@bdslaundry.com

\*X voltage can be connected to 1 or 3 phase power and operates on 1 phase only.

# PREMIUM SINGLE TUMBLE DRYERS

SPECIFICATIONS	UT050	UT055	UT075	UTF75 FAST DRY
Control Options	UniLinc	UniLinc	UniLinc	UniLinc
Capacity - lb (kg)	50 (25)	55 (24)	75 (34)	75 (34)
Overall Width - in (mm)	38.5 (980)	34.5 (876)	38.5 (980)	38.5 (980)
Overall Depth - in (mm)	46.8 (1190)	53.1 (1350)	53.0 (1350)	53.0 (1350)
Overall Height - in (mm)	77.3 (1960)	66.7 (1700)	77.3 (1960)	77.3 (1960)
Cylinder Diameter - in (mm)	37.0 (940)	33 (838)	37.0 (940)	37.0 (940)
Cylinder Depth - in (mm)	30.0 (762)	35.0 (889)	36.0 (914)	36.0 (914)
Cylinder Volume - cu ft (liters)	18.7 (530)	17.3 (490)	22.4 (634)	22.4 (634)
Reversing Cylinder	Option	Option	Option	Standard
Water Inlet Size (C.A.R.E.™ System)	(1) 3/4"-11 1/2" NH Hose Connection	(1) 3/4"-11 1/2" NH Hose Connection	(1) 3/4"-11 1/2" NH Hose Connection	(1) 3/4"-11 1/2" NH Hose Connection
Heat Input Power	Gas 122,000 Btu/hr Steam 113,600 Btu/hr Electric 30 kW	112,000 Btu/hr - 27 kW	165,000 Btu/hr 133,920 Btu/hr 30 kW	225,000 Btu/hr - -
Gas Connections - in (npt)	0.5	0.5	0.5	0.75
Plumbing Connections - Steam - in (npt)	0.75	-	0.75	-
Air Outlet - in (mm)	8 (200)	8 (200)	8 (200)	10 (254)
Motor - HP	Fan 0.5 Cylinder 0.5	0.5 0.5	0.5 0.5	1.5 0.5
Airflow - cfm (liters/sec)	700	700	800	1100
Electrical Specs - amps	Gas and Steam B 100-120V/50-60/1 9 X* 200-240V/50-60/1-3 6 N 440-480V/50-60/3 3 Q 200-240/50-60/3 - Electric D 200-208V/50-60/1 - E 230-240V/50-60/1 91 F 200-208V/50-60/3 87 G 230-240V/50-60/3 75 K 440V/50-60/3 41 L 460-480V/50-60/3 38	12 7 3 - 133 116 78 67 37 34	12 7 3 - - - 104 90 49 45	- - 7 6 - - 104 90 49 45
Shipping Dimensions Approx - in (mm)	Width 41.5 (1054) Depth 50.0 (1270) Height Gas & Electric - 81.0 (2057) Steam - 83.5 (2121)	35.5 (902) 57 (1448) 70.5 (1791)	41.5 (1054) 56.0 (1422) Gas & Electric - 81.0 (2057) Steam - 83.5 (2121)	41.5 (1054) 56.0 (1422) 81.0 (2057)
Net Weight - lb (kg)	Gas & Steam 660 (299), 690 (313) Electric 680 (308)	430 (195), 430 (195) 440 (200)	690 (313), 710 (322) 720 (327)	700 (320) -
Shipping Weight - lb (kg)	Gas & Steam 710 (322), 740 (336) Electric 730 (331)	470 (215), 470 (215) 480 (220)	740 (336), 760 (345) 770 (349)	750 (340) -
Agency Approvals	CSA	CSA	CSA	CSA



(800) 688-0020 · info@bdslaundry.com

\*X voltage can be connected to 1 or 3 phase power and operates on 1 phase only.

# UT SERIES PREMIUM TUMBLE DRYERS 120-200 LB

SPECIFICATIONS		UT120	UT170	UT200
Control Options		UniLinc, M Series	UniLinc, M Series	UniLinc, M Series
Capacity - lb (kg)		120 (55)	170 (77)	200 (90)
Cylinder Diameter - in (mm)		44 (1120)	50.8 (1290)	50.8 (1290)
Cylinder Depth - in (mm)		41 (1040)	42.5 (1080)	50 (1270)
Cylinder Volume - cu ft (liters)		36.1 (1020)	49.8 (1410)	58.6 (1660)
Overall Width - in (mm)		46.1 (1170)	52.9 (1345)	52.9 (1345)
Overall Depth - in (mm)		67.9 (1725)	69.8 (1772)	77.3 (1965)
Overall Height - in (mm)		85.7 (2175)	94 (2390)	94 (2390)
Door Opening Size		26.9 (683)	26.9 (683)	26.9 (683)
Water Inlet Size (C.A.R.E.™ System)		(1) 3/4"-11 1/2" NH Hose Connection	(1) 3/4"-11 1/2" NH Hose Connection	(1) 3/4"-11 1/2" NH Hose Connection
Energy Data	Gas Models	270,000 Btu/hr	395,000 Btu/hr	425,000 Btu/hr
	Steam Models	187,560 Btu/hr	265,563 Btu/hr	265,564 Btu/hr
	Electric Models	60 kW	-	-
Utility Connection - in (mm)	Gas Models	1 NPT	1 NPT (13)	1 NPT (13)
	Steam Models	0.75 NPT	0.75 NPT (inlet), 1 NPT (outlet)	0.75 NPT (inlet), 1 NPT (outlet)
Air Outlet - in (mm)		10 (254)	12 (305)	12 (305)
Motor - HP (W)	Fan	1.5	1.5	1.5
	Cylinder	1.5	1.5	1.5
Airflow - cfm		1400	2150	2150
Electrical Specifications - Amps	Gas & Steam Models			
	<b>Q</b> 200-240V/50-60/3	7	11	12
	<b>N</b> 440-480V/50-60/3	4	6	6
	Electric Models			
	<b>G</b> 230-240V/50-60/3	147	-	-
	<b>K</b> 440V/50-60/3	82	-	-
<b>L</b> 460-480V/50-60/3	75	-	-	
Net Weight - lb (kg)	Gas & Electric	1220 (555)	1400 (635)	1550 (705)
	Steam	1330 (605)	1550 (705)	1700 (770)
Standard Shipping Weight - lb (kg)	Gas	1290 (585)	1480 (670)	1630 (740)
	Steam	1400 (635)	1630 (740)	1780 (805)
	Electric	1320 (600)	-	-
Shipping Dimensions Approx - in (mm)	Width	48 (1220)	52.1 (1320)	52.1 (1320)
	Depth	71.5 (1820)	73.8 (1870)	81.3 (2070)
	Height	90 (2290)	99 (2510)	99 (2510)
Agency Approvals		CSA	CSA	CSA

**TO LEARN MORE OR TO FIND A DISTRIBUTOR IN YOUR AREA, VISIT [UNIMAC.COM](http://UNIMAC.COM)  
ALLIANCE LAUNDRY SYSTEMS - SHEPARD ST, RIPON, WI 54971 - 1.800.587.5458**

Consult your UniMac distributor for details. For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems at Alliance Laundry Systems are registered to ISO 9001.



(800) 688-0020 • [info@bdslaundry.com](mailto:info@bdslaundry.com)