

UC SERIES HARDMOUNT WASHER-EXTRACTORS 20-80 LB

SPECIFICATIONS		UC20	UC30	UC40	UC60	UC80
Control Option		M9	M9	M9	M9	M9
Capacity - lb (kg)		20 (9)	30 (13.6)	40 (18)	60 (27)	80 (36)
Overall Width - in (mm)		26 (660)	29 (737)	30.6 (777)	34.1 (866)	41.5 (1054)
Overall Depth - in (mm)		30.9 (785)	35.3 (897)	42.3 (1074)	44.7 (1135)	47.1 (1196)
Overall Height - in (mm)		43 (1092)	45 (1143)	47.2 (1199)	49.9 (1267)	57.2 (1453)
Cylinder Diameter - in (mm)		21 (533)	24 (610)	26.3 (668)	30 (762)	36 (916)
Cylinder Depth - in (mm)		13.8 (351)	16 (406)	20.3 (516)	22 (559)	21.9 (556)
Cylinder Volume - cu ft (liters)		2.8 (79)	4.2 (119)	6.3 (178)	9.0 (255)	12.9 (365)
Door Opening Size - in (mm)		11.6 (295)	14.3 (363)	16.3 (414)	16.3 (414)	18.5 (470)
Door Bottom to Floor - in (mm)		14.4 (366)	14 (356)	14.6 (371)	14.9 (378)	17.9 (455)
Water Inlet Connection - in (mm)		2 x 0.75 (19)	2 x 0.75 (19)	2 x 0.75 (19)	4 x .75 (19)	4 x .75 (19)
Drain Diameter - in (mm)		1 x 3 (76)	1 x 3 (76)	1 x 3 (76)	1 x 3 (76)	1 x 3 (76)
Drain Center Height to Floor - in (mm)		3.9 (99)	4.3 (109)	4.5 (114)	4.9 (124)	5.1 (130)
Motor Power - HP (kW)		1 (0.75)	1 (0.75)	2 (1.5)	3 (2.25)	5 (3.75)
Total # of Speeds		6, 9	6, 9	6, 9	6, 9	6, 9
Cylinder Speed RPM (G-Force)	Gentle	37 (0.4)	34 (0.4)	33 (0.4)	31 (0.4)	28 (0.4)
	Wash	51 (0.8)	48 (0.8)	46 (0.8)	43 (0.8)	39 (0.8)
	Distribution	92 (2.5)	86 (2.5)	82 (2.5)	77 (2.5)	70 (2.5)
	Very Low Extract	301 (27)	282 (27)	269 (27)	252 (27)	230 (27)
	Low Extract	518 (80)	485 (80)	464 (80)	434 (80)	396 (80)
	Medium Extract	579 (100)	542 (100)	518 (100)	485 (100)	443 (100)
	High Extract	648 (125)	606 (125)	579 (125)	542 (125)	495 (125)
	Very High Extract	710 (150)	664 (150)	635 (150)	594 (150)	542 (150)
	Ultra High Extract	819 (200)	766 (200)	733 (200)	686 (200)	626 (200)
Voltage/Circuit Breaker FLA	B 120/60/1	15-9	15-12	20-15	N/A	N/A
	X 200-240/50-60/1-3	15-4 (1 Ph) 15-3 (3 Ph)	15-7 (1 Ph) 15-4 (3 Ph)	15-7 (1 Ph) 15-4 (3 Ph)	15-11 (1 Ph) 15-7 (3 Ph)	20-15 (1 Ph) 15-9 (3 Ph)
	N 440-480/50/60/3	15-2	15-3	15-3	15-4	15-6
Shipping Dimensions - in (mm)	Width	28 (711)	31.5 (800)	32.5 (826)	37.5 (953)	44 (1118)
	Depth	33.8 (859)	38.3 (973)	43.5 (1105)	46.9 (1191)	54.5 (1384)
	Height	49.4 (1255)	51.3 (1303)	53.6 (1361)	56.3 (1430)	59.6 (1514)
Net Weight - lb (kg)		340 (154)	440 (200)	540 (245)	680 (308)	1250 (567)
Standard Shipping Weight - lb (kg)		380 (172)	480 (218)	580 (263)	720 (327)	1300 (590)
Slat Crate Shipping Weight - lb (kg)		460 (209)	580 (263)	680 (308)	840 (381)	1430 (649)
Agency Approvals		cULus	cULus	cULus	cULus	cULus

**TO LEARN MORE OR TO FIND A DISTRIBUTOR IN YOUR AREA, VISIT UNIMAC.COM
ALLIANCE LAUNDRY SYSTEMS - SHEPARD ST, RIPON, WI 54971 - 1.800.587.5458**

Consult your UniMac distributor for details. For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems at Alliance Laundry Systems are registered to ISO 9001.



(800) 688-0020 • info@bdsiaundry.com