

UY SERIES SOFTMOUNT WASHER-EXTRACTORS 20-70 LB

SPECIFICATIONS	UY20	UY25	UY30	UY40	UY55	UY70
Control	PROform	PROform	PROform	PROform	PROform	PROform
Capacity - lb (kg)	20 (8)	25 (11)	30 (14)	40 (18)	55 (24)	70 (31)
Dimensions	-	-	-	-	-	-
Width - in (mm)	27 15/16 (710)	31 5/16 (795)	31 5/16 (795)	38 3/16 (970)	38 3/16 (970)	38 3/16 (970)
Depth - in (mm)	31 1/8 (790)	31 5/16 (795)	37 3/16 (945)	38 3/16 (970)	43 1/2 (1105)	46 5/8 (1185)
Height - in (mm)	43 7/8 (1115)	48 1/4 (1225)	48 1/4 (1225)	55 1/2 (1410)	55 1/2 (1410)	55 1/2 (1410)
Cylinder Diameter - in (mm)	20 7/8 (530)	24 3/8 (620)	24 3/8 (620)	29 1/2 (750)	29 1/2 (750)	29 1/2 (750)
Cylinder Depth - in (mm)	13 3/4 (350)	13 3/4 (350)	17 3/4 (450)	16 (410)	21 1/2 (545)	24 1/2 (620)
Cylinder Volume - cu. ft. (liters)	2.6 (75)	3.7 (105)	4.8 (135)	6.4 (180)	8.5 (240)	9.9 (280)
Door Opening Size - in (mm)	13 (330)	16 1/8 (410)	16 1/8 (410)	18 1/8 (460)	18 1/8 (460)	18 1/8 (460)
Door Bottom to Floor - in (mm)	13 3/4 (349)	13 1/2 (342)	13 1/2 (342)	18 3/4 (477)	18 3/4 (477)	18 3/4 (477)
Wash Speed - RPM	49	49	49	42	42	42
Extract Speed - RPM	1165	1075	1075	980	980	915
Extract G-Force	400	400	400	400	400	350
Water Inlet Conn. - in (mm)	2 x 3/4 (19)	2 x 3/4 (19)	2 x 3/4 (19)	2 x 3/4 (19)	2 x 3/4 (19)	2 x 3/4 (19)
Steam Inlet Conn. - in (mm)	1/2 (13)	1/2 (13)	1/2 (13)	1/2 (13)	1/2 (13)	1/2 (13)
Drain Conn. Size - in (mm)	3 (76)	3 (76)	3 (76)	3 (76)	3 (76)	3 (76)
Motor Size - HP (kW)	1.00 (0.75)	1.48 (1.10)	2.01 (1.50)	2.95 (2.20)	4.02 (3.00)	4.02 (3.00)
Voltage/Hz/Phase Circuit	200-240V 50/60Hz 1/3ph	200-240V 50/60Hz 1/3ph	200-240V 50/60Hz 1/3ph	200-240V 50/60Hz 1/3ph	200-240V 50/60Hz 1/3ph 440-480V 50/60Hz 3ph	200-240V 50/60Hz 1/3ph 440-480V 50/60Hz 3ph
Shipping Dimensions	-	-	-	-	-	-
Height - in (mm)	49 (1245)	52 15/16 (1345)	52 15/16 (1345)	61 (1550)	61 (1550)	61 (1550)
Width - in (mm)	29 1/2 (750)	32 7/8 (835)	32 7/8 (835)	40 3/8 (1025)	40 3/8 (1025)	40 3/8 (1025)
Depth - in (mm)	33 1/16 (840)	33 1/16 (840)	38 3/4 (985)	40 (1015)	45 1/4 (1150)	48 1/4 (1225)
Net Weight - lb (kg)	408 (185)	463 (210)	563 (255)	838 (380)	948 (430)	1092 (495)
Shipping Weight - lb (kg)	441 (200)	518 (235)	606 (275)	871 (395)	992 (450)	1135 (515)
Agency Approvals	CSA	CSA	CSA	CSA	CSA	CSA

**TO LEARN MORE OR TO FIND A DISTRIBUTOR IN YOUR AREA, VISIT UNIMAC.COM
ALLIANCE LAUNDRY SYSTEMS - SHEPARD ST, RIPON, WI 54971 - 1.800.587.5458**

For the most accurate information, the installation guide should be used for all design and construction purposes.
Due to continuous product improvements, design and specifications subject to change without notice.
The quality management systems at Alliance Laundry Systems are registered to ISO 9001.



(800) 688-0020 • info@bdslaundry.com

UY SERIES SOFTMOUNT WASHER-EXTRACTORS 90-275 LB

SPECIFICATIONS	UY90	UY125	UY180	UY230	UY275
Control	PROform	PROform	PROform	PROform	PROform
Capacity - lb (kg)	90 (40)	125 (55)	180 (80)	230 (100)	275 (120)
Tilt Option			Option	Option	Option
Dimensions w/o Tilt	-	-	-	-	-
Width - in (mm)	47 (1195)	47 (1195)	58 7/8 (1495)	70 1/2 (1790)	73 (1855)
Depth - in (mm)	56 1/2 (1430)	63 3/8 (1610)	76 3/8 (1940)	78 15/16 (2005)	82 1/8 (2085)
Height - in (mm)	75 (1905)	75 (1905)	78 1/8 (1985)	81 1/8 (2060)	82 1/8 (2085)
Dimensions w/ Tilt	-	-	-	-	-
Width - in (mm)			61 5/8 (1565)	72 7/8 (1855)	74 9/16 (1895)
Depth - in (mm)			93 11/16 (2380)	99 3/4 (2534)	100 1/2 (2553)
Height - in (mm)			97 1/2 (2476)	101 3/8 (2575)	103 1/2 (2628)
Cylinder Diameter - in (mm)	36 (914)	36 (914)	43 11/16 (1110)	47 1/4 (1200)	51 3/16 (1300)
Cylinder Depth - in (mm)	24 (610)	31 1/8 (790)	33 (838)	33 7/8 (860)	34 1/4 (870)
Cylinder Volume - cu. ft. (liters)	14.1 (400)	18.3 (518)	28.5 (807)	34.3 (972)	40.8 (1154)
Door Opening Size - in (mm)	21 5/16 (540)	21 5/16 (540)	20 7/8 (530)	20 7/8 (530)	25 5/8 (650)
Door Bottom to Floor - in (mm)	28 3/4 (730)	28 3/4 (730)	40 1/8 (1020)	43 1/8 (1095)	42 1/2 (1080)
Wash Speed - RPM	38	38	36	33	32
Extract Speed - RPM	830	830	750	720	695
Extract G-Force	350	350	350	350	350
Water Inlet Conn. - in (mm)	3 x 1 (25)	3 x 1 (25)	3 x 1 1/2 (38)	3 x 1 1/2 (38)	3 x 1 1/2 (38)
Steam Inlet Conn. - in (mm)	3/4 (19)	3/4 (19)	1 (25)	1 (25)	1 (25)
Drain Conn. Size - in (mm)	2 x 3 (76)	2 x 3 (76)	2 x 4 (103)	2 x 4 (103)	2 x 4 (103)
Motor Size - HP (kW)	10.06 (7.50)	10.06 (7.50)	14.75 (11.00)	20.12 (15.00)	24.81 (18.50)
Voltage/Hz/Phase Circuit/	220-240V/50-60Hz/3ph 400-480V/50/60Hz/3ph	220-240V/50-60Hz/3ph 400-480V/50/60Hz/3ph	208-240V/50-60Hz/3ph 400-480V/50/60Hz/3ph	208-240V/50-60Hz/3ph 400-480V/50/60Hz/3ph	208-240V/50-60Hz/3ph 400-480V/50/60Hz/3ph
Shipping Dimensions w/o Tilt	-	-	-	-	-
Height - in (mm)	82 15/16 (2105)	82 15/16 (2105)	86 5/8 (2200)	92 5/16 (2345)	92 1/8 (2340)
Width - in (mm)	56 5/16 (1430)	56 5/16 (1430)	66 1/2 (1690)	73 7/16 (1865)	78 3/4 (2000)
Depth - in (mm)	61 13/16 (1570)	68 7/8 (1750)	76 3/4 (1950)	83 11/16 (2125)	85 7/16 (2170)
Shipping Dimensions w/ Tilt	-	-	-	-	-
Height - in (mm)			96 1/16 (2440)	98 (2490)	98 (2490)
Width - in (mm)			66 1/2 (1690)	80 5/16 (2040)	80 5/16 (2040)
Depth - in (mm)			81 11/16 (2075)	93 1/2 (2375)	93 1/2 (2375)
Net Weight - lb (kg) w/o Tilt	3439 (1560)	3594 (1630)	5820 (2640)	6989 (3170)	7672 (3480)
Net Weight - lb (kg) w/ Tilt			6592 (2990)	7760 (3520)	8466 (3840)
Shipping Weight - lb (kg) w/o Tilt	3748 (1700)	3902 (1770)	6239 (2830)	7518 (3410)	8179 (3710)
Shipping Weight - lb (kg) w/ Tilt			7077 (3210)	8289 (3760)	8951 (4060)
Agency Approvals	CSA	CSA	CSA	CSA	CSA

**TO LEARN MORE OR TO FIND A DISTRIBUTOR IN YOUR AREA, VISIT UNIMAC.COM
ALLIANCE LAUNDRY SYSTEMS - SHEPARD ST, RIPON, WI 54971 - 1.800.587.5458**

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems at Alliance Laundry Systems are registered to ISO 9001.