

STACKED WASHER-EXTRACTOR/TUMBLE DRYERS

SPECIFICATIONS	UST30		UST50	
	WASHER-EXTRACTOR	TUMBLE DRYER	WASHER-EXTRACTOR	TUMBLE DRYER
Control Option	M4		M4	
Capacity - lb (kg)	30 (13) x 2		50 (23) x 2	
Overall Width - in (mm)	31.4 (797)		34.4 (875)	
Overall Depth - in (mm)	45.5 (1152)		51.3 (1302)	
Overall Height - in (mm)	79.7 (2023)		84.3 (2141)	
Cylinder Diameter - in (mm)	24.0 (610)	30.0 (762)	26.3 (668)	33.0 (838)
Cylinder Depth - in (mm)	16.0 (406)	26.0 (660)	20.3 (515)	30.0 (762)
Cylinder Volume - cu ft (liters)	4.2 (119)	10.6 (300)	6.3 (178)	14.8 (419)
Reversing Cylinder	-	Standard	-	Standard
Door Opening Size - in (mm)	14.3 (363)	22.6 (574)	16.3 (414)	26.9 (683)
Door Bottom to Floor - in (mm)	14.0 (356)	51.3 (1303)	14.6 (370)	52.3 (1328)
Water Inlet Connection - in (mm)	2 x 0.75 (19)	-	2 x 0.75 (19)	-
Drain Diameter - in (mm)	1 x 3 (76)	-	1 x 3 (76)	-
Drain Center Height to Floor - in (mm)	4.3 (108)	-	4.5 (115)	-
Heat Input Power - Btu/hr (kW, Mi/hr.)	-	73,000 (21.4, 77.0)	-	95,000 (27.8, 100)
Gas Connection - in	-	1/2 NPT	-	1/2 NPT
Air Outlet - in (mm)	-	8.0 (200) Elliptical	-	10.0 (250) Elliptical
Airflow - cfm (l/sec)	-	400 (190)	-	600 (285)
Motor - HP (kW)	Fan	-	0.5 (0.4)	-
	Drive	1 (0.75)	0.3 (0.2)	2 (1.5)
Total # of Speeds	6	-	6	-
Cylinder Speeds - RPM (G-Force)	Gentle	34 (0.4)	-	33 (0.4)
	Wash	48 (0.8)	-	46 (0.8)
	Distribution	86 (2.5)	-	82 (2.5)
	Very Low	282 (27)	-	269 (27)
	Low	485 (80)	-	464 (80)
	Medium	542 (100)	-	518 (100)
Electric Specs - amps	B 100-120V/50/60/1	15	15	-
	X 200-240V/50/60/3	15	10	15
	P 380-415V/50/60/3	15	10	15
Shipping Dimensions - in (mm)	Width	34.5 (876)		35.5 (902)
	Depth	47.0 (1194)		54.0 (1372)
	Height	83.0 (2108)		89.0 (2261)
Net Weight - lb (kg)	770 (349)		910 (413)	
Shipping Weight - lb (kg)	787 (357)		930 (422)	
Agency Approvals	UL _{us}		CSA	UL _{us} CSA

**TO LEARN MORE, VISIT UNIMAC.COM OR CALL 1.800.587.5458.
ALLIANCE LAUNDRY SYSTEMS - SHEPARD ST, RIPON, WI 54971**

Consult your UniMac distributor for details. For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems at Alliance Laundry Systems are registered to ISO 9001.



(800) 688-0020 • info@bdslaundry.com