

# Electrolux 220-300 G-force Washers

## X-Series Solid-Mount, Extra Spin for Coin/Card

### Heavy-duty, built to last, and saves up to 50% on water – automatically.

Electrolux Professional 220-300 G-Force high-speed extraction, solid-mount washers minimize drying time and provide significant electrical and gas savings. Self-service laundries benefit from faster throughput (freeing up dryers, folding tables and parking spots) which creates higher profits. Your customers can even receive a text message (option) notifying them when their wash is done and ready for unloading! Increase your profits and create customers for life with the unique features of Electrolux Professional washers. Electrolux X-Series washers are built to take the abuse of a demanding coin laundry environment and to provide years and years of trouble-free operation.

#### FEATURES AND BENEFITS:

- AS (Automatic Savings) - saves up to 50% on water. With every wash cycle, AS determines the actual weight of the load and adds precisely the right amount of water significantly reducing water consumption and energy costs (available on 65 & 80 lb. models only)
- Extremely low water and energy consumption
- Convenient four compartment detergent box
- Large, secure coin box
- 220-300 G-force extraction removes more water, saving energy & time in dryer
- Heavy-duty construction with robust steel door and lock, hinges set wide apart
- Stainless and galvanized steel in all vital parts for maximum rust protection
- SuperBalance guarantees the correct extraction force, longer machine life – on 65 lbs only
- Power Balance ensures the correct extraction and maximum savings in drying time. Minimizes stress on machines for trouble free operation – on 80 lbs and up
- Sanitizing Rinse for greater customer satisfaction and additional revenue
- **Options:** Text Messaging, Voice Guidance, and LaundryPulse

#### COMPASS PRO MICROPROCESSOR OFFERS:

- Easy to customize programs
- Large display and one control knob for easy program selection
- More than 20 languages available – displays two languages, simultaneously
- Real time clock for time of day pricing, happy hour pricing and promotions
- Heavy Soil and Extra Rinse option buttons for higher customer satisfaction and increased revenue
- Detailed user statistics and programmability




Available in 65, 80, and 135 lb. capacities.  
\*The 135 lb model does NOT have AS.\*



Designed by experts. Inspired by you.



| Electrolux "X" Models, 300G   | W5280X             |             | W5350X             |              | W5600X         |             |
|---|--------------------|-------------|--------------------|--------------|----------------|-------------|
| Capacity (lb/kg)  | 65                 | 30          | 80                 | 36           | 135            | 60          |
| Width (in/mm)   | 36 3/4             | 933         | 43 7/8             | 1115         | 46 3/16        | 1173        |
| Depth (overall) (in/mm)   | 38 3/4             | 985         | 44 1/8             | 1121         | 50 5/8         | 1286        |
| Height (in/mm)  | 57 5/16            | 1456        | 61 13/16           | 1570         | 65 7/8         | 1673        |
| Height to bottom of door (in/mm)  | 20 1/2             | 520         | 21                 | 534          | 21 1/4         | 540         |
| Door opening diameter (in/mm)   | 16 1/8             | 410         | 21 1/16            | 535          | 21 1/16        | 535         |
| Cylinder volume (ft <sup>3</sup> /l)  | 9.9                | 280         | 12.4               | 350          | 21.2           | 600         |
| Drain outlet diameter (in/mm)   | 2 15/16            | 75          | 2 15/16            | 75           | 2 15/16        | 75          |
| Height to centerline of drain (in/mm)   | 4 11/16            | 119         | 4 13/16            | 122          | 4 1/16         | 103         |
| Extract (rpm/G-Force)   | 805 / 300          |             | 650 / 220          |              | 630 / 220      |             |
| Dynamic floor load (lb/kN)  | 1101 +/- 2135      | 4.9 +/- 9.5 | 1551 +/- 2405      | 6.9 +/- 10.7 | 2248 +/- 3507  | 10 +/- 15.6 |
| Dynamic frequency (Hz)  | 13.4               |             | 10.8               |              | 10.5           |             |
| Noise level (dBA) in extraction   | <75                |             | <82                |              | <84            |             |
| Crated width - (in/mm)  | 43 5/16            | 1100        | 44 7/8             | 1140         | 47 5/8         | 1210        |
| Crated depth - (in/mm)  | 45 11/16           | 1160        | 54 5/16            | 1380         | 55 1/8         | 1400        |
| Crated height - (in/mm)   | 62 5/8             | 1590        | 67 11/16           | 1720         | 72 13/16       | 1850        |
| Crated weight (lb/kg)   | 882                | 401         | 1272               | 579          | 1920           | 873         |
| <b>Electrical Requirements (standard)</b>   |                    |             |                    |              |                |             |
| Voltage/frequency/phase   | 208-240/60/1 or 3~ |             | 208-240/60/1 or 3~ |              | 208-240/60/3~  |             |
| Power (kW) / Full-load current (A) / Ckt breaker (A)  | 1.5 / 7.2 / 15     |             | 1.8 / 8.6 / 15     |              | 2.6 / 7.2 / 15 |             |
| Voltage/frequency/phase   | 480 / 60 / 1 or 3~ |             | 480/60/1 or 3~     |              | 480/60/3~      |             |
| Power (kW) / Full-load current (A) / Ckt breaker (A)  | 1.5 / 3.1 / 10     |             | 1.8 / 3.8 / 10     |              | 2.6 / 3.1 / 10 |             |
| <b>Water Information</b>  |                    |             |                    |              |                |             |
| Inlet fittings (* = 3 inlets)   | 3/4"               | DN20        | 3/4"               | DN20         | 1"             | DN25        |
| Flow (gpm/lpm @ 45 psi) (each inlet)  | 16                 | 60          | 16                 | 60           | 25             | 110         |
| Recommended water pressure (psi/kPa)  | 30 - 90            | 200-600     | 30 - 90            | 200-600      | 30 - 90        | 200-600     |
| Approx Water usage (gal / liters @ full load)   | n/a                |             |                    |              |                |             |
| Modified Energy Factor  |                    |             |                    |              |                |             |
| Water Factor (Gal per cycle/drum volume)  |                    |             |                    |              |                |             |
| <p>Refer installation and servicing to qualified, licensed personnel. Always read installation and operating manuals and consult local codes before installation. Protect machines with properly rated, common-trip, circuit breakers ONLY. Warranty void if not properly installed. Solid-mount machines require a concrete foundation, and are not suitable for upper-floor or above-basement installations. Contact us for more information and for availability of machines for electric services not listed. Specifications subject to change without notice. Laundrylux assumes no responsibility for errors or omissions in this information.</p>  |                    |             |                    |              |                |             |

## Electrolux Professional Line 5000 The all-in-one business solution for your self-service laundry.



### Manage your business easier

- Analyze machine utilization
- View revenue data and reports
- Remotely adjust pricing and promotions
- Get real-time statistics on machine status
- Receive alerts by text or email



### Greatest flexibility with Compass Pro™

- Real-time clock for time-of-day and happy hour pricing
- Multi-language menu selection
- Easy to customize
- Simple to use
- Revenue generating option buttons



### Extended lifetime due to Super Balance / Power Balance™

- Lower maintenance costs
- Less vibration
- Maximum water extraction
- Lower energy costs



### Cost savings in water & energy with Automatic Savings (AS)

- Determines load weight and adds precisely the correct amount of water
- Up to 50% water savings – automatically
- Reduces water and energy consumption

Please contact your local authorized Electrolux Professional Distributor.

For Electrolux Professional Laundry Solutions in North America:

**Laundrylux**  
800.381.7222 • laundrylux.com

Laundrylux • 461 Doughty Blvd., Inwood, NY 11096-0338  
T 516-371-4400 • F 516-371-4204 • sales@laundrylux.com

Parts: 516-371-2000 • F 516-371-4029 • parts@laundrylux.com

Technical Care: 516-371-0700 • F 516-371-4029 • techcare@laundrylux.com

En Mexico: Llame gratis a este numero 001-800-010-1010



(800) 688-0020 • info@bdslaundry.com